


Low voltage halogen pin base lamp

RJL 20W/12/SKY/GY6.35

Radium

Product Datasheet Date: 24.03.2023



G



300



2800K



2 000h

General Data

Article No.	22320006
Code	RJL 20W/12/SKY/GY6.35
Product EAN	4008597200069
Customs tariff no.	85392198
Box quantity (pcs.)	40
EAN Box	4008597600067
Gross weight of box in kg	0.205
Length of box in m	0.144
Width of box in m	0.107
Height of box in m	0.121
ETIM class	EC000259
ETIM class name	Low voltage halogen lamp without reflector
Weight	2 g
Product status	● Active

Electric Parameters

Rated wattage	20.0 W
Weighted energy consumption in 1,000 hours	20 kWh

Low voltage halogen pin base lamp

RJL 20W/12/SKY/GY6.35

Radium

Electric Parameters

Nominal voltage	12 V
Lamp voltage	12-12 V
Nominal current	1667 mA

Light Application Parameters

Luminous flux	300 lm
Rated lamp luminous flux	300 lm
Luminous efficiency	15 lm/W
Colour temperature	2800 K
Color coordinate X	0,452
Color coordinate Y	0,409

Service Life

Average nominal lifespan	2000 h
No. switching cycles	50000

Specification

Energylabel notice	current label, with EPREL registration
Energy Label A to G	G
Diameter	12 mm
Total length	44 mm
Model	Clear
Base	GY6.35

Information especially for EPREL

Energylabel notice	current label, with EPREL registration
--------------------	--

Miscellaneous

EU-date of phase-out	01.09.2023
----------------------	------------

Notes

Standard low voltage halogen pin base lamp, 12V operation with transformer, base GY6.35, stepless dim, 2000 h mean service life

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.


The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Low voltage halogen pin base lamp

RJL 20W/12/SKY/GY6.35

Radium

Base




GY6.35
IEC/EN 60061-1
sheet 7004-59-6

Spectrum


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

Incandescent lamps have got a continuous red-dominated spectrum as the light is generated by heating up a tungsten filament. The addition of halogens to the filling gas enhance the efficiency and prevents blackening. Further increase in efficiency can be achieved by adding Xenon and/or IRC-coating.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



light of incandescent lamps



daylight(D 65)

General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.