


## TUNGSTEN HALOGEN LAMPS • MR-14 AND MR-18 REFLECTOR


### JCR SERIES

- Only for Use in Approved Enclosed Halogen Fixtures
- Operate in Horizontal Position
- 2-Pin Vented Base - G7.9
- 2-Pin Vented Base - GX7.9
- 45mm and 57mm Dichroic Coated Reflector

Watts	Ushio Ordering Code	Ushio Lamp Code	Dimensions mm			Reflector Type	Filament Type	Working Distance mm	Color Temp K	Avg Life h	Burn Position
			Dia (A)	OAL (B)	Ref. (C)						
<b>MR-14 &amp; MR-18, 2-Pin Vented Base – G7.9 Line Voltage</b>											
150	1000206	DNE, JCR120V-150W	57.2	49.9	15.9	Specular	CC-8	69.1	3350	12	Horiz
250	1000057	BHB, JCR120V-250W	44.5	47.5	15.9	Specular	CC-8	65.8	3400	50	Horiz
<b>MR-14 &amp; MR-18, 2-Pin Vented Base – GX7.9 Low Voltage</b>											
150	1000207	DNF, JCR21V-150W	57.2	45.1	15.9	Specular	CC-6	69.1	3400	25	Horiz
150	1000325	ELZ, JCR21V-150W	57.2	45.1	15.9	Specular	CC-6	69.1	3350	60	Horiz



G7.9



GX7.9

