



GE  
Lighting



## Discharge - Single Ended Hot Restrike

CSR 1200 SE/HR/UV- C

# 27764

---

### Product information

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering,  $R_a > 90$ , and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance -Available with UV blocking.

---



## Product data

EAN Code	0043168277648
DUN Code	10043168277645
Bulb Shape	Globe
Bulb Finish	Clear
Bulb Diameter [mm]	42
Cap/Base	G38
Dimming Capability	No
Gross weight per piece [g]	440
Maximum Overall Length [mm]	200
Net weight per piece [g]	390
Brand	General Electric (GE)

## Performance data

Nominal power [W]	1200
Nominal lamp voltage [V]	100
Nominal lumens [lm]	110000
Nominal correlated colour temperature (CCT) [K]	5600
Colour Rendering Index (CRI) [Ra]	90
Colour Code	956
Arc Gap	10
Ballast Required	Yes
Operating position	U - Universal
Nominal chromaticity coordinate X	0.333
Nominal chromaticity coordinate Y	0.333
Energy efficiency class (EEC)	A+
Lamp Current [A]	12
Light Center Length [mm]	107
Weighted energy consumption [kWh/1000h]	1320

## Logistic data

Pack Quantity	6
Pallet quantity EUR (PC)	240
Pallet quantity UK (PC)	360
Inner pack type	BOX
Outer pack type	OUTER BOX
Outer case size	280 x 190 x 305 (mm)
Layer quantity	48 EUR, 72 UK
Layer quantity EUR	48
Layer quantity UK	72
Product status	Available

## Application areas



Film and Broadcast

## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

## Disclaimer

Special Purpose Lamp, Not suited for household illumination