



PAR 56 240PAR56/WFL 12V

20577

# **Product information**

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent







# **Product data**

DUN Code	00043168205771
Bulb Shape	PAR
Bulb Finish	Aluminized
Bulb Diameter [mm]	177.8
Cap/Base	Screw terminal
Nominal beam angle [°]	30
Gross weight per piece [g]	687
Maximum Overall Length [mm]	127
Net weight per piece [g]	547
Brand	General Electric (GE)

# Performance data

Nominal power [W]	240
Nominal lamp voltage [V]	12
Nominal lumens [lm]	2570
Rated Life [h]	2000
Ballast Required	Yes
Nominal center beam candlepower (CBCP) [cd]	13000
Coil type	C-6
Energy efficiency class (EEC)	E
Weighted energy consumption [kWh/1000h]	260.08

# Logistic data

Product status	Available	
Layer quantity UK	1	
Layer quantity	1 UK	
Outer case size	349 × 300 × 446 (mm)	
Pallet quantity UK (PC)	324	
Pack Quantity	12	





### **Application areas**



### **Downloads & Links**

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

#### Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.