

Fig. 4



Fig. 5




Fig. 7




Fig. 8




Fig. 6

Watts	Bulb OD	GE Description	Footnotes/ Safety Notices	ANSI Code	LIF Code	Product Order Code	Std. Pack Qty.	MOL (mm)	Design Volts	Design Color Temp (K)	Rated Life (hrs)	Initial Design Lumens	Fila-ment Type	Lighted Length (mm)	Bulb Finish	Burning Position	Fig. No.
Table 4: Halogen, Double-Ended, C-8, R7s Base, 119mm (4¹¹/₁₆" MOL (continued)																	
1000	T-3	FCM-Q1000T3/4CL	62	FCM	P2/28	23797	12	119	120	3200	400	28000	C-8	60		H4	4
		FHM-Q1000/T3/4	15, 31, 62	FHM	P2/29	23792	12	119	120	3200	400	27300	C-8		Frosted	H4	4
		EJD-Q1000T3/3CL (185V)	52, 62	EJD	—	23788	12	119	185	3350	100	33600	C-8	68		H4	4

Table 5: Halogen, Double-Ended, C-8, R7s Base, 167mm (6⁹/₁₆" MOL																	
675	T-3	FFT/HIR-Q675T3/4	52, 62	—	—	20884	6	167	120	3250	400	26400	C-8	67		H4	5
1000	T-3	FFT-Q1000T3/1CL	62	FFT	—	33280	12	167	120	3200	400	26400	C-8	67		H4	5
1500	T-4	FDB-Q1500T4/4CL	62	FDB	—	23841	12	167	120	3200	400	41250	C-8	62		H4	5
		FGT-Q1500T4/4	15, 62	FGT	—	41229	12	167	120	3200	400	40200	C-8		Frosted	H4	5

Watts	Bulb OD	GE Description	Footnotes/ Safety Notices	ANSI Code	LIF Code	Product Order Code	Std. Pack Qty.	MOL (mm)	Design Volts	Design Color Temp (K)	Rated Life (hrs)	Initial Design Lumens	Fila-ment Type	Lighted Length (mm)	Bulb Finish	Burning Position	Fig. No.
Table 6: Halogen, Double-Ended, C-8, R7s Base, 189mm (7⁷/₁₆" MOL																	
625	T-3	Q625T3/4CLP2/10	62		P2/10	19697	12	189	230	3200	300	16900	C-8	107		H4	6
		Q625T3/4CLP2/10	62		P2/10	19698	12	189	240	3200	300	16900	C-8	107		H4	6
1000	T-3	EKM-Q1MT3/4CLP2/7	62	EKM	P2/7	20249	12	189	230	3200	300	28000	C-8	115		H4	6
		EKM-Q1MT3/4CLP2/7	62	EKM	P2/7	20253	12	189	240	3200	300	28000	C-8	115		H4	6
1250	T-3	Q1250T3/P2/12	62		P2/12	19695	12	189	230	3200	300	35000	C-8	112		H4	6
		Q1250T3/P2/12	62		P2/12	19696	12	189	240	3200	300	35000	C-8	112		H4	6

Watts	Bulb OD	GE Description	Footnotes/ Safety Notices	ANSI Code	LIF Code	Product Order Code	Std. Pack Qty.	Base Type	Design Volts	Design Color Temp (K)	Rated Life (hrs)	Initial Design Lumens	Fila-ment Type	LCL (mm)	MOL (mm)	Burning Position	Bulb Finish	Fig. No.
Table 7: Halogen, Single-Ended, G5.3 Miniature 2-Pin (5.3mm apart)																		
30	T-3.5	DZA	62	DZA	—	37346	24	G5.3	10.8	3100	400	530	C-6	27	51	BDTHCH		
250	G-6	EYH/FKT	62	EYH	—	13617	24	G5.3	120	3000	200	6000	CC-6	36	64	BDTHCH		7
500	G-6	FBG/FBD	62	FBG	—	33663	24	G5.3	120	3200	50	13200	CC-6	44	76	ANYCH		7
600	G-7	DYH	62	DYH	—	30364	24	G5.3	120	3200	75	17000	CC-6	36	64	ANYCH		7
650	G-6	DVY	62	DVY	—	30304	24	G5.3	120	3300	25	20000	CC-6	36	64	BDTHCH		7

Table 8: Halogen, Single-Ended, G9.5 Medium 2-Pin (9.5mm apart)																		
500	T-6	EHD-Q500CL/TP	62	EHD		39768	24	G9.5	120	2900	2000	10000	CC-8	60	105	Any		8
		EHC-Q500/5CL	62	EHC		39789	24	G9.5	120	3150	500	12700	CC-8	60	105	Any		8

Lamp stocking color code: EUROPE ONLY, EUROPE and NORTH AMERICA, NORTH AMERICA ONLY