

Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14

Watts	Bulb OD	GE Description	Footnotes/ Safety Notices	ANSI Code	LIF Code	Product Order Code	Std. Pack Qty.	Base Type	Design Volts	Design Color Temp (K)	Rated Life (hrs)	Initial Design Lumens	Fila- ment Type	LCL (mm)	MOL (mm)	Burning Position	Bulb Finish	Fig. No.
Table 9: Halogen, Single-Ended, G9.5/Heat Sink (Metal 2-Pin) (continued)																		
575	T-6	HPL575/C 115V	62	—	—	92431	12	G9.5/HS	115	3200	300	16500	4-C8	60	106	Any		10
		HPL575/C 120V	62	—	—	92433	12	G9.5/HS	120	3200	300	16520	4-C8	60	106	Any		10
		HPL575/LL/C 115V	62	—	—	92434	12	G9.5/HS	115	3050	2000	12360	4-C8	60	106	Any		10
		HPL575/LL/C 120V	62	—	—	92435	12	G9.5/HS	120	3050	2000	12360	4-C8	60	106	Any		10
		HPL575	62	—	—	37128	12	G9.5/HS	230	3200	300	14900	6-C8	60	106	Any		11
		HPL575	62	—	—	37131	12	G9.5/HS	240	3200	300	14900	6-C8	60	106	Any		11
		HPL575-X LL	62	—	—	37817	12	G9.5/HS	230	3050	1500	11780	6-C8	60	106	Any		11
		HPL575-X LL	62	—	—	37818	12	G9.5/HS	240	3050	1500	11780	6-C8	60	106	Any		11
750	T-6	HPL750/C 115V	7, 62	—	—	92432	12	G9.5/HS	115	3200	300	22000	4-C8	60	106	Any		10
		HPL750/LL/C	7, 62	—	—	92770	12	G9.5/HS	115	3050	2000	16400	4-C8	60	106	Any		10
		HPL750	7, 62	—	—	37824	12	G9.5/HS	230	3200	300	19750	6-C8	60	106	Any		11
		HPL750	7, 62	—	—	37826	12	G9.5/HS	240	3200	300	19750	6-C8	60	106	Any		11
		HPL750-XLL-C	7, 62	—	—	92768	12	G9.5/HS	230	3050	1500	15600	6-C8	60	106	Any		11
		HPL750-XLL-C	7, 62	—	—	92769	12	G9.5/HS	240	3050	1500	15600	6-C8	60	106	Any		11