

HF-Performer II for TL-D lamps

HF-Performer 118 TL-D EII 220-240V 50/60Hz

Slim, lightweight High Frequency electronic ballast for TL-D fluorescent lamps, based on EII technology



Product data

• General Characteristics

Rated Number of Lamps	1 piece
Rated Ballast-Lamp Power	18
Rated Lamptype	TL-D
Application code	EII
Line Voltage	220-240 V
Line Frequency	50/60 Hz
Housing	L 280x30x28
Ignition Method	Warm Start
Lifetime 90% surv.@Tcaselife	50000 hr
Energy Efficiency Index	A2

• Operating Characteristics

Automatic restart	Yes
Battery voltage running lamps	176-254
Battery voltage lamp ignition	198-254 V
Constant wattage deviation	-2%/+2%
Inrush current Peak	18 (max) A
Inrush current Width	0.25 ms
Max ballast on MCB(16A type B)	28 x
Earth leakage current	0.5 mA
Mains voltage safety (AC)	-10%/+10%
Mains voltage performance (AC)	-8%/+6%
Overvoltage protection 320Vac	48 hr

Overvoltage protection 350Vac	2 hr
PowerFactor 100% output power	0.96 -
Power losses gear	3.0 W
Ballast Lumen Factor	0.95 -
Crestfactor	1.7 (max) -
Ignition time	0.55 (max) s
Operating frequency	45 kHz
Total Harmonic Distortion EUR	15 %
Hum and Noise level	Inaudible

• Wiring Characteristics

Cable-Cap output-wires to earth	200 pF
Cable-Cap output-wires mutual	200 pF
Conn.type input terminals	WAGO 251 universal connector [Suitable for both automatic wiring (ALF and ADS) and manual wiring]
Conn.type output terminals	WAGO 251 universal connector [Suitable for both automatic wiring (ALF and ADS) and manual wiring]
Striplength	8.0-9.0 mm
Dual fixture Master/Slave	Possible, lamp wires 3m max. length [Master/Slave operation possible]
Wcs Input terminals	0.50-1.00 mm ²
Wcs Output terminals	0.50-1.00 mm ²
Wcs auto insertion (ALF/ADS)	0.50 mm ²

• Temperature Characteristics

T-case life	75 C
-------------	------



asimpleswitch.com

PHILIPS

sense and simplicity

HF-Performer II for TL-D lamps

T-case maximum	75 (max) C
T-ignition	-25 (min), 50 (max) C
T-ambient	-25 (min), 50 (max) C
T-storage	-40 (min), 80 (max) C

• Approval & Application Chars

EMI 9kHz .. 30 MHz	EN 55015
EMI 30 MHz .. 1000MHz	EN 55022 level B [Level = Class]
Safety Standard	IEC 61347-2-3
Performance Standard	IEC 60929
Quality Standard	ISO 9000:2000
Environmental Standard	ISO 14001
Harmonic current emissions	IEC 61000-3-2
EMC Immunity	IEC 61547
Vibrations	IEC 68-2-6 Fc
Bumps	IEC 68-2-29 Eb
Humidity	EN 61347-2-3 clause 11
Approval marks	ENEC / VDE-EMV
CE marking	Yes
Temperature marking	110 [Yes]
Emergency standard	IEC 60598-2-22


• Product Dimensions

Length A1	280.0 mm
Fixing Hole Distance	265.0 mm
Length A2	
Width B1	30.0 mm
Height C1	28.0 mm
Fixing Hole Diameter D1	4.2 mm

• Product Data

Order code	913700191066
Full product code	913700191066
Full product name	HF-P 118 TL-D EII 220-240V 50/60Hz
Order product name	HF-P 118 TL-D EII 220-240V 50/60Hz
Pieces per pack	1
Packing configuration	12
Packs per outerbox	12
Bar code on pack - EAN1	8711500934086
Bar code on outerbox - EAN3	8711500934093
Logistic code(s) - 12NC	913700191066
Net weight per piece	0.198 kg
Successor order code	911589 00

Dimensional drawing



Product	A1 (Norm)	A2 (Norm)	B1 (Norm)	C1 (Norm)	D1 (Norm)
HF-P 118 TL-D EII 220-240V 50/60Hz	280.0	265.0	30.0	28.0	4.2



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, May 14
data subject to change