



# HF-Performer Intelligent for TL5 HE/HO lamps

HF-Performer Intelligent 3/4 14/24 TL5/PL-L EII 220-240V

Intelligent, flat, slim, high frequency electronic ballast for TL5 fluorescent lamps

## Product data

### • General Characteristics

Rated Number of Lamps	3/4 piece
Rated Ballast-Lamp Power	14/24
Rated Lamptype	TL5/PL-L
Application code	EII
Line Voltage	220-240 V
Line Frequency	50/60 Hz
Housing	L 360x30x22
Ignition Method	Warm Start
Lifetime 90% surv.@Tcaselife	50000 hr
Energy Efficiency Index	A2

### • Operating Characteristics

Automatic restart	Yes
Battery voltage running lamps	198-276
Constant wattage deviation	-2%/+2%
Inrush current Peak	45 (max) A
Inrush current Width	0.4 ms
Max ballast on MCB(16A type B)	12 x
Earth leakage current	0.5 (max) mA
Mains voltage safety (AC)	-10%/+10%
Mains voltage performance (AC)	-8%/+6%
Crestfactor	1.7 (max) -
Ignition time	5.0 (max) s
Hum and Noise level	Inaudible

### • Wiring Characteristics

Cable-Cap output-wires to earth	200 pF
Cable-Cap output-wires mutual	200 pF
Conn.type input terminals	Insert
Conn.type output terminals	Insert
Max. cable length Device/Lamp	2 m
Max. cable length Hot Wires	0.75 m
Striplength	8.0-9.0 mm
Wcs Input terminals	0.50-1.00 mm <sup>2</sup>
Wcs Output terminals	0.50-1.00 mm <sup>2</sup>

### • Temperature Characteristics

T-case life	75 C
T-case maximum	75 (max) C
T-ignition	-25 (min), 50 (max) C
T-ambient	-25 (min), 50 (max) C
T-storage	-40 (min), 80 (max) C

### • Approval & Application Chars

EMI 9kHz .. 30 MHz	EN 55015
EMI 30 MHz .. 1000MHz	EN 55022 Class B
Safety Standard	IEC 61347-2-3
Performance Standard	IEC 60929
Quality Standard	ISO 9000:2000
Environmental Standard	ISO 14001



[asimpleswitch.com](http://asimpleswitch.com)

# PHILIPS

sense and simplicity

# HF-Performer Intelligent for TL5 HE/HO lamps

Harmonic current emissions	IEC 61000-3-2
EMC Immunity	IEC 61547
Vibrations	IEC 68-2-6 Fc
Bumps	IEC 68-2-29 Eb
Humidity	EN 61347-2-3 clause 11
Approval marks	ENEC / VDE-EMV
CE marking	Yes
Temperature marking	110 [Yes]
Emergency standard	IEC 60598-2-22


## • Product Dimensions

Length A1	360 mm
Fixing Hole Distance	350 mm
Length A2	
Width B1	30 mm
Height C1	22 mm
Fixing Hole Diameter	4.2 mm
D1	

## • Product Data

Order code	913700657666
Full product code	913700657666
Full product name	HF-Pi 3/4 14/24 TL5/PL-L EII 220-240V
Order product name	HF-Pi 3/4 14/24 TL5/PL-L EII 220-240V
Pieces per pack	1
Packing configuration	12
Packs per outerbox	12
Bar code on pack - EAN1	8711500881960
Bar code on outerbox - EAN3	8727900887754
Logistic code(s) - 12NC	913700657666
Net weight per piece	0.285 kg

## Dimensional drawing



Product	A1 (Norm)	A2 (Norm)	B1 (Norm)	C1 (Norm)	D1 (Norm)
HF-Pi 3/4 14/24 TL5/PL-L EII 220-240V	360	350	30	22	4.2



© 2011 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2011, June 7  
data subject to change