

Hi-Spot 95 Superia Extralife

Hi-Spot 95 75W FL30°

0021231



Range features

- Halogen light without the need for a transformer
- Unique, patented, spiral faceted aluminised reflector
- 100% dimmable
- For use in mains voltage E27 cap downlights, spotlights and luminaires
- Use dichroic lamps for lighting food, textiles and other objects sensitive to heat
- Suitable for outdoor use when protected from direct contact with water
- Average rated life 3000 hrs - 50% longer life than conventional halogen PAR lamps

PRODUCT OVERVIEW

Ordering number	0021231
CRI (%)	100
Dimmable	Yes
Colour temperature (K)	2900
Bulb finish	Aluminium
Nominal average life (h)	3000
EAN code	54 102882 12319
Bulb shape	Reflector
Cap/Base	E27
Type	HI-SPOT 95
Watt (W)	75
Beam angle(°)	30
Voltage (V)	230
Beam angle(°)	30
Luminous flux (lm)	640
Lamp Length (mm) - C/L	91
Lamp Diameter (mm) - D	97

Hi-Spot 95 Superia Extralife

Hi-Spot 95 75W FL30°

0021231**DATA TABLE****General data**

Ordering number	0021231
Recommendation for disposal at end of life	Not applicable
Special purpose lamp	No
Average rated life (h)	3000
No. of switching cycles before premature failure (min)	>12000x
Type	HI-SPOT 95
Starting time (max) (s)	0
Transformer required	No
Product name	Hi-Spot 95 75W FL30°
Long description	Halogen light without the need for a transformer. Unique, patented, spiral faceted aluminised reflector. 100% dimmable. For use in mains voltage E27 cap downlights, spotlights and luminaires. Use dichroic lamps for lighting food, textiles and other objects sensitive to heat. Suitable for outdoor use when protected from direct contact with water. Average rated life 3000 hrs - 50% longer life than conventional halogen PAR lamps
Intended purpose	General lighting
Warm-up time to 60% of full light (max) (s)	Instant Full Light
Unit case	15
Lamp mercury content (mg)	0
Cap/Base	E27
Bulb shape	Reflector
Breakage cleaning instructions	Not applicable
Bulb finish	Aluminium
Ballast required	No
Nominal average life (h)	3000
Dimmable	Yes
EAN code	5410288212319
IEC Reference 2	IEC 60432-3
IEC Reference	IEC 60357
Fixture rating	Open
Energy class	D
IEC Reference 3	IEC 60630

Hi-Spot 95 Superia Extralife

Hi-Spot 95 75W FL30°

0021231

Optical data

Peak intensity (cd)	2200
Rated luminous flux (lm)	640
Beam angle(°)	30
Luminous flux (lm)	640
Lumen maintaining at end of nominal Life (lm)	80
CRI (%)	100
Beam angle(°)	30
Colour temperature (K)	2900

Electrical data

Voltage (V)	230
Rated watt (W)	75.0
Watt (W)	75
Lamp power factor	1
Current (A)	0.33

Physical data

Packaging outer length (cm)	48
Packaging single length (cm)	8.6
Packaging outer height (cm)	11
Packaging single width (cm)	8.6
Packaging single height (cm)	9.6
Packaging outer width (cm)	28.5
Lamp Length (mm) - C/L	91
Lamp Diameter (mm) - D	97


Hi-Spot 95 Superia Extralife

Hi-Spot 95 75W FL30°

0021231

PHOTOMETRY

Hi-Spot 95 - 75W/30°



Hi-Spot 95 Superia Extralife

Hi-Spot 95 75W FL30°

0021231

TECHNICAL DRAWINGS

