

HMI 250 W/SE

HMI | Metal halide lamps, | single-ended



Areas of application

- Film and television recording in daylight conditions, in the studio or outdoors
- Film and TV production (high-wattage lamps)
- Stage (lighting for dramatic effect)
- Entertainment

Product benefits

- Very high luminous efficacy of up to 100 lm/W

Product features

- Color temperature: approx. 6,000 K (Daylight)
- Dimmable
- Hot restart capability
- High color rendering index: $R_a >$



Technical data



Electrical data

Nominal wattage	250 W
Nominal voltage	50 V
Nominal current	5.40 A

Light technical data

Nominal luminous flux	16200 lm
Luminous flux	16200 lm
Color temperature	6000 K

Dimensions & weight



Product line drawing

Base

Diameter	12.0 mm
Length	84.0 mm

Lifespan

Lifespan	250 h
----------	-------

Additional product data

Base (standard designation)	FaX1.5
Picto Studio	Yes

Certificates & standards

EEL – Energy Label	B
--------------------	---

Product datasheet


Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300239064	OSRHMI250SE	-	-	-


Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.



Burning position



Burning position

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4050300239064	HMI 250 W/SE	Shipping carton box 1	150 mm x 142 mm x 202 mm	4.30 dm ³	611.75 g
4050300730363	HMI 250 W/SE	Shipping carton box 10	225 mm x 210 mm x 235 mm	11.10 dm ³	1227.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

Further information can be found in the following brochures, obtainable on request from OSRAM:

“Technology and applications/Metal halide lamps”

“Guidelines for control gear and igniters for metal halide lamps”

“Availability of control gear and igniters”

“Rome. 8 pm. Overcast. No problem. HMI lamps”

“High Noon” HMI 12.000 and 18.000 W/SE/GX51

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.