

CLEO HPA 400 S 1CT

Product family description Medium- pressure metal halide radiators with iron and cobalt additives

Product Features

- Run- up time 4 minutes
- A few minutes of cooling is required before re-ignition

Product Benefits

• Emit ozone- free radiation mainly between 300 and 400 nm

Luminaires

- A suitable filter must be used to provide protection against the emitted UV-B and UV-C radiationForced cooling is required, especially when used in
- enclosed equipment

System

• A ballast and an ignitor are required

Application

Suntanning equipment

Product data		
Order code	192202 45	
Full product code	871150019220245	
Full product name	CLEO HPA 400 S 1CT	-
Order product name	CLEO HPA 400 S 1CT/4	
Packing type	1 Carton	
Pieces per pack	1	
Packing configuration	4	-
Packs per outerbox	4	
Bar code on pack - EAN1	8711500192202	
Bar code on intermediate packing - EAN2		
Bar code on outerbox - EAN3	8711500192219	-
Logistic code(s) - 12NC	9280 751 06005	
ILCOS code		
Net weight per piece	0.016 (KG)	-
Successor order code		
Technical Type	400	
Execution	S [S]	
Packing Type	1CT [1 Carton]	
Packing Configuration	4	
Cap-Base	RX7s	
Cap-Base Information	-	
Burning Position	p10	



Product data		
Main Application	Suntanning	
Additional Information	-	
Product Nett Weight[gr]	20	
Rated Lamp Wattage[W]	400	
Technical Lamp Power[W]	400	
Lamp Voltage[V]	133	
Lamp Current[A]	3.4	

