

HSR 1200 W/60

HSR | Metal halide lamps



Areas of application

- Entertainment
- Archtainment

Product benefits

- Outer bulb for ease of handling

Product features

- Single-ended lamps similar to HTI lamps



Product datasheet

Technical data


Electrical data

Nominal wattage	1200 W
Nominal voltage	95 V
Nominal current	12.70 A

Light technical data

Nominal luminous flux	110000 lm
Luminous flux	110000 lm
Color temperature	6000 K
Luminance	20000 cd/cm ²

Dimensions & weight



Product line drawing

Diameter	40.0 mm
Length	175.0 mm

Lifespan

Lifespan	1000 h
----------	--------

Additional product data

Base (standard designation)	G22
Picto Studio	Yes

Capabilities

Burning position	hs30
------------------	------

Product datasheet

Certificates & standards

EEI – Energy Label	B
--------------------	---


Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300526836	OSRHSR120060	-	-	-

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HSR lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions. HSR lamps are not capable of hot restarts.



Burning position

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4050300526836	HSR 1200 W/60	Folding carton box 1	74 mm x 73 mm x 200 mm	1.08 dm ³	231.00 g
4050300526843	HSR 1200 W/60	Shipping carton box 20	300 mm x 225 mm x 370 mm	24.98 dm ³	4459.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.