

## Blacklight BL368 FEP Toughcoat

F15W T5 BL368 TOUGHCOAT

0001650



### Range Features

- Features
- Excellent fragment retention in the event of breakage
- The protective FEP coating meets the IEC60068-2-75 Pendulum Hammer test (5 Joule) and the 4m drop test, demonstrating excellent glass retention in the event of accidental lamp breakage
- The 97% UV-A transmission of FEP maintains maximum insect attraction
- No discolouration or yellowing of shatter resistant coating during the entire lamp life (> 10,000 hrs)
- The FEP material does not degrade during life. Versions employing PET coatings become brittle, and may not contain fragments. PET is also less transparent for UV- radiation
- The coating withstands up to 200°C in both open and enclosed IP65 fittings.
- The melting temperature is 260°C
- Meets all necessary regulations for resistance to heat and fire, and does not support combustion when exposed to naked flame or excessive heat. It passes the 850°C Glow Wire Test
- Satisfies the requirements of the International Food Standard (IFS 2004)
- FDA approved, in compliance with 21CFR177.1550 Regulatory Compliance Status
- Satisfies the requirements of the BRC (British Retail Consortium) leading supermarkets global standard. In paragraph 3.2.2.6.2 it states All bulbs and strip lights, including those on electric fly killer units, where they constitute a risk to products, shall be protected by shatterproof plastic diffusers, sleeve covers or with a shatterproof protective coating
- Applications
- Insect attraction in restaurants, kitchens, food shops, supermarkets
- Food processing plants
- Pharmaceutical industry
- The risk of glass and mercury contamination is strongly decreased
- Help to avoid injury and loss of production time



### PRODUCT OVERVIEW

Lamp finish	FEP Toughcoated
Dimmable	Yes
EAN code	5410288016504
Cap/Base	G5
Watt (Nominal) (W)	15
Ordering number	0001650
Voltage (V)	44

### DATA TABLE

General data

Control gear required	Yes
Lamp finish	FEP Toughcoated

## Blacklight BL368 FEP Toughcoat

F15W T5 BL368 TOUGHCOAT

**0001650**

<b>Dimmable</b>	Yes
<b>EAN code</b>	5410288016504
<b>Cap/Base</b>	G5
<b>Ordering number</b>	0001650
<b>Range features</b>	<p><b>Features</b>            Excellent fragment retention in the event of breakage            The protective FEP coating meets the IEC60068-2-75 Pendulum Hammer test (5 Joule) and the 4m drop test, demonstrating excellent glass retention in the event of accidental lamp breakage            The 97% UV-A transmission of FEP maintains maximum insect attraction            No discolouration or yellowing of shatter resistant coating during the entire lamp life (&gt; 10,000 hrs)            The FEP material does not degrade during life. Versions employing PET coatings become brittle, and may not contain fragments. PET is also less transparent for UV- radiation            The coating withstands up to 200°C in both open and enclosed IP65 fittings.            The melting temperature is 260°C            Meets all necessary regulations for resistance to heat and fire, and does not support combustion when exposed to naked flame or excessive heat. It passes the 850°C Glow Wire Test            Satisfies the requirements of the International Food Standard (IFS 2004)            FDA approved, in compliance with 21CFR177.1550 Regulatory Compliance Status            Satisfies the requirements of the BRC (British Retail Consortium) leading supermarkets global standard. In paragraph 3.2.2.6.2 it states All bulbs and strip lights, including those on electric fly killer units, where they constitute a risk to products, shall be protected by shatterproof plastic diffusers, sleeve covers or with a shatterproof protective coating</p> <p><b>Applications</b>            Insect attraction in restaurants, kitchens, food shops, supermarkets            Food processing plants            Pharmaceutical industry            The risk of glass and mercury contamination is strongly decreased            Help to avoid injury and loss of production time</p>
<b>Product name</b>	F15W T5 BL368 TOUGHCOAT
<b>Sales pack quantity</b>	25
<b>E-number FI</b>	4940440
<b>Electrical data</b>	
<b>Watt (Nominal) (W)</b>	15
<b>Voltage (V)</b>	44

## Blacklight BL368 FEP Toughcoat

F15W T5 BL368 TOUGHCOAT

**0001650**

### Physical data

<b>Single packaging type</b>	Box/Sleeve
<b>Weight (kg)</b>	0.02

### TECHNICAL DRAWINGS

