

Aquastar T8

F38W/Aquastar

0002185



Range Features

- Light colour: 10000 Kelvin (simulating the tropical light spectrum)
- Promotes the growth of coral and aquatic plants through natural red and blue sections of the light spectrum
- Excellent lighting performance
- Applications
- For all biological organisms in fresh and marine water aquariums



PRODUCT OVERVIEW

| Lamp finish | Coated |
|----------------------------|---------------|
| Lamp shape | Tubular |
| Colour temperature (K) | 10000 |
| Dimmable | Yes |
| EAN code | 5410288021850 |
| Cap/Base | G13 |
| Туре | AquaStar |
| Watt (Nominal) (W) | 38 |
| Ordering number | 0002185 |
| Luminous flux (Rated) (lm) | 2100 |
| Voltage (V) | 104 |

DATA TABLE

| Gen | eral | da | ta |
|-----|------|----|----|
| | | | |

| Average life (Nominal) (h) | 10000 |
|----------------------------|---------------|
| Control gear required | Yes |
| Lamp finish | Coated |
| Lamp shape | Tubular |
| Dimmable | Yes |
| EAN code | 5410288021850 |
| Fixture rating | Open |
| IEC Reference | IEC 60081 |



Aquastar T8

F38W/Aquastar

0002185

| IEC Reference 2 | IEC 61195 |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cap/Base | G13 |
| Lamp mercury content (mg) | 10 |
| Туре | AquaStar |
| Ordering number | 0002185 |
| Range features | Light colour: 10000 Kelvin (simulating the tropical light spectrum) Promotes the growth of coral and aquatic plants through natural red and blue sections of the light spectrum Excellent lighting performance Applications For all biological organisms in fresh and marine water aquariums |
| Product name | F38W/Aquastar |
| Special purpose lamp | Yes |
| Transformer required | No |
| Sales pack quantity | 25 |
| E-number SE | 8356655 |
| Optical data | |
| Colour temperature (K) | 10000 |
| Luminous flux (Nominal) (lm) | 2100 |
| Luminous flux (Rated) (lm) | 2100 |
| Electrical data | |
| Current (A) | 0.43 |
| Watt (Nominal) (W) | 38 |
| Watt (Rated) (W) | 38 |
| Voltage (V) | 104 |
| Physical data | |
| Max. Lamp Diameter (mm) - D | 26 |
| Lamp Langth (mm) C/I | 10010 |
| Lamp Length (mm) - C/L | 1061.2 |
| Length base to base (mm) - A | 1061.2 1047 |
| | |
| Length base to base (mm) - A | 1047 |

TECHNICAL DRAWINGS

