

Micro-Lynx CFL

MICRO-LYNX 827 GX53 6W SLV

0035901



Range Features

-



PRODUCT OVERVIEW

Lamp finish	Clear
Lamp shape	Disc
Colour temperature (K)	2700
CRI (Ra)	80
Dimmable	No
EAN code	5410288359014
Energy class	A
Cap/Base	GX53
Type	GX53
Watt (Nominal) (W)	6
Light colour	827 Homelight
Ordering number	0035901
Efficacy (Rated) (lm/w)	39
Average life (Rated) (h)	10000
Luminous flux (Rated) (lm)	235
Technology	Compact Fluorescent
Voltage (V)	220-240

DATA TABLE

General data

Average life (Nominal) (h)	10000
Control gear required	NO
Lamp finish	Clear
Lamp shape	Disc
Dimmable	No
Dry applications use only	Yes
EAN code	5410288359014

Micro-Lynx CFL

MICRO-LYNX 827 GX53 6W SLV

0035901

Energy class	A
Energy saving lamp	Yes
General application	Hospitality; Residential & Consumer;
Intended purpose	General lighting
Cap/Base	GX53
Lamp mercury content (mg)	< 2,5 mg
Type	GX53
No. of switching cycles before premature failure (min)	10000
Ordering number	0035901
Product name	MICRO-LYNX 827 GX53 6W SLV
Average life (Rated) (h)	10000
Starting time (max) (s)	0,9-1,5 s
Technology	Compact Fluorescent
Transformer required	No
Sales pack quantity	20
Warm-up time to 60% of full light (max) (s)	4 s
E-number SE	8357589

Optical data

Colour temperature (K)	2700
CRI (Ra)	80
Light colour	827 Homelight
Lumen maintenance at end of nominal life (%)	85
Luminous flux (Nominal) (lm)	235
Luminous flux (Rated) (lm)	235

Electrical data

kWh per 1000 hours burning time	6
Lamp power factor	0.6
Watt (Nominal) (W)	6
Efficacy (Rated) (lm/w)	39
Watt (Rated) (W)	6
Voltage (V)	220-240

Physical data

Max. Lamp Diameter (mm) - D	75,2 max.
Lamp Length (mm) - C/L	15,2 mm
Single packaging type	Box/Sleeve
Weight (kg)	0.05
Outer package dimensions (L x W x H) (cm)	28.00 x 19.50 x 9.20

Micro-Lynx CFL

MICRO-LYNX 827 GX53 6W SLV

0035901

Single package dimensions (L x W x H) 8.10 x 8.10 x 2.70
(cm)

TECHNICAL DRAWINGS

