

## Aquastar T8

F30W/Aquastar  
0002225



### Range Features

- Light colour: 10000 Kelvin (simulating the tropical light spectrum)
- Promotes the growth of coral and aquatic plants through natural red and blue sections of the light spectrum
- Excellent lighting performance
- Applications
- For all biological organisms in fresh and marine water aquariums



### PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	Tubular
Colour temperature (K)	10000
Dimmable	Yes
EAN code	5410288022253
Cap/Base	G13
Type	AquaStar
Watt (Nominal) (W)	30
Ordering number	0002225
Luminous flux (Rated) (lm)	1700
Voltage (V)	96

### DATA TABLE

#### General data

Average life (Nominal) (h)	10000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288022253
Fixture rating	Open
IEC Reference	IEC 60081

## Aquastar T8

F30W/Aquastar  
0002225

<b>IEC Reference 2</b>	IEC 61195
<b>Cap/Base</b>	G13
<b>Lamp mercury content (mg)</b>	10
<b>Type</b>	AquaStar
<b>Ordering number</b>	0002225
<b>Range features</b>	Light colour: 10000 Kelvin (simulating the tropical light spectrum) Promotes the growth of coral and aquatic plants through natural red and blue sections of the light spectrum Excellent lighting performance Applications For all biological organisms in fresh and marine water aquariums
<b>Product name</b>	F30W/Aquastar
<b>Special purpose lamp</b>	Yes
<b>Transformer required</b>	No
<b>Sales pack quantity</b>	25
<b>E-number SE</b>	8356653
<b>E-number FI</b>	4943010

### Optical data

<b>Colour temperature (K)</b>	10000
<b>Luminous flux (Nominal) (lm)</b>	1700
<b>Luminous flux (Rated) (lm)</b>	1700

### Electrical data

<b>Current (A)</b>	0.37
<b>Watt (Nominal) (W)</b>	30
<b>Watt (Rated) (W)</b>	30
<b>Voltage (V)</b>	96

### Physical data

<b>Max. Lamp Diameter (mm) - D</b>	26
<b>Lamp Length (mm) - C/L</b>	908.8
<b>Length base to base (mm) - A</b>	894.4
<b>Length base to pin Min-Max - B</b>	899.3-901.7
<b>Single packaging type</b>	Box/Sleeve
<b>Weight (kg)</b>	0.12

## TECHNICAL DRAWINGS

## Aquastar T8

F30W/Aquastar  
**0002225**

