

Hi-Spot ES50 Home

ES50 HM 230V 50W 25° GU10 SV1

0021256



Range Features

- Unique, patented, spiral faceted aluminised reflector
- Clear front lens for crisp sparkling light
- Integral safety fuse
- Ceramic base
- For use in mains voltage GU10 downlights, spotlights and luminaires
- Transformer free operation
- Average rated life 2500hrs



PRODUCT OVERVIEW

Lamp finish	Aluminium
Lamp shape	Reflector
Colour temperature (K)	2700
CRI (Ra)	100
Dimmable	Yes
EAN code	5410288212562
Energy class	D
Cap/Base	GU10
Beam angle(°)	25
Type	PAR16 (GU10)
Watt (Nominal) (W)	50
Light colour	827 Homelight
Ordering number	0021256
Average life (Rated) (h)	3000
Luminous flux (Rated) (lm)	300
Technology	Halogen
Voltage (V)	230

DATA TABLE

General data

Average life (Nominal) (h)	3000
Control gear required	No
Lamp finish	Aluminium
Lamp shape	Reflector
Dimmable	Yes
EAN code	5410288212562
Energy class	D
Energy saving lamp	No

Hi-Spot ES50 Home

ES50 HM 230V 50W 25° GU10 SV1

0021256

Fixture rating	Open
General application	Residential & Consumer;Hospitality;
IEC Reference	IEC 60357
IEC Reference 2	IEC 60432-3
IEC Reference 3	IEC 60630
Intended purpose	General lighting
Cap/Base	GU10
Lamp mercury content (mg)	0
Type	PAR16 (GU10)
No. of switching cycles before premature failure (min)	> 12000
Ordering number	0021256
Range features	<p>Unique, patented, spiral faceted aluminised reflector Clear front lens for crisp sparkling light Integral safety fuse Ceramic base For use in mains voltage GU10 downlights, spotlights and luminaires Transformer free operation Average rated life 2500hrs</p>
Product name	ES50 HM 230V 50W 25° GU10 SV1
Average life (Rated) (h)	3000
Special purpose lamp	No
Starting time (max) (s)	0
Technology	Halogen
Transformer required	no
Sales pack quantity	10
Warm-up time to 60% of full light (max) (s)	Instant Full Light
E-number FI	4749548

Optical data

Colour temperature (K)	2700
CRI (Ra)	100
Beam angle(°)	25
Light colour	827 Homelight
Lumen maintenance at end of nominal life (%)	80
Luminous flux (Nominal) (lm)	300
Peak intensity (cd)	1100
Luminous flux (Rated) (lm)	300
Suitable for accent lighting	Yes
Beam angle (Rated) (°)	25

Hi-Spot ES50 Home

ES50 HM 230V 50W 25° GU10 SV1

0021256


Electrical data

kWh per 1000 hours burning time	50
Lamp power factor	1
Watt (Nominal) (W)	50
Watt (Rated) (W)	50
Voltage (V)	230

Physical data

Max. Lamp Diameter (mm) - D	50
Lamp Length (mm) - C/L	55
Single packaging type	Box/Sleeve
Weight (kg)	0.05
Lamp dimension equal to filament lamp equivalent	Yes
Designed for optimum use in non standard conditions	No
Outer package dimensions (L x W x H) (cm)	50.00 x 27.00 x 14.00
Single package dimensions (L x W x H) (cm)	6.20 x 4.80 x 4.80

TECHNICAL DRAWINGS



Hi-Spot ES50 Home

ES50 HM 230V 50W 25° GU10 SV1

0021256

