

PAR 56 Mains Voltage

PAR 56 300W MFL 240V

0060514



Range Features

- Pressed glass reflector lamps
- Beam patterns: from very narrow spot through wide angle floods
- Consistency from lamp to lamp
- Instant replaceability without the need to re-focus and re-aim fixtures
- Applications
- Theatre lighting
- TV and studio
- Entertainment and Architectural applications
- Displays
- Museums
- Churches
- Towers
- Exhibitions
- Gardens
- Discos
- Directions for use
- Easy handling
- Can be used with very economical fixtures (PAR cans)



PRODUCT OVERVIEW

Beam angle(°)	Medium Flood
Colour temperature (K)	2750
EAN code	5410288605142
Cap/Base	GX16d
Type	PAR 56
Watt (Nominal) (W)	300
Ordering number	0060514
Voltage (V)	240

DATA TABLE

General data

Average life (Nominal) (h)	2000
Burning position	Any
EAN code	5410288605142
Cap/Base	GX16d
Type	PAR 56
Ordering number	0060514

PAR 56 Mains Voltage

PAR 56 300W MFL 240V

0060514

Range features	<p>Pressed glass reflector lamps Beam patterns: from very narrow spot through wide angle floods Consistency from lamp to lamp Instant replaceability without the need to re-focus and re-aim fixtures Applications Theatre lighting TV and studio Entertainment and Architectural applications Displays Museums Churches Towers Exhibitions Gardens Discos Directions for use Easy handling Can be used with very economical fixtures (PAR cans)</p>
Product name	PAR 56 300W MFL 240V
Sales pack quantity	12

Optical data

Beam angle(°)	Medium Flood
Colour temperature (K)	2750
Peak intensity (cd)	30000

Physical data

Max. Lamp Diameter (mm) - D	178.6
Lamp Length (mm) - C/L	127
Single packaging type	Box/Sleeve
Weight (kg)	0.47
Outer package dimensions (L x W x H) (cm)	62.00 x 47.00 x 18.00
Single package dimensions (L x W x H) (cm)	14.50 x 15.00 x 15.00

Electrical data

Watt (Nominal) (W)	300
Watt (Rated) (W)	300
Voltage (V)	240

TECHNICAL DRAWINGS

PAR 56 Mains Voltage

PAR 56 300W MFL 240V

0060514

