



# Product Description

## HalogenA IDE

Mains-voltage high-wattage double-envelope giving a white halogen light

### Features

- Quartz burner with a linear tungsten filament in a single-ended thermal-shock-resistant clear glass tubular envelope
- High luminous efficacy
- Excellent colour rendering


### Application

- Typical application: outdoor floodlighting such as sport grounds, car parks, building sites, harbours and airport aprons
- Also used in Indoor applications: public halls, factories, sport halls etc.

## Related products



## Dimensional drawing



Product	C (Max)	D (Norm)	D (Max)
IDE 1000W E40 230V T38 CL	260	-	38.5

## Compare table

Order code	Full product name	Bulb	Bulb Finish	Cap-Base	Burning Position	Voltage	Lamp Wattage	Lamp Current	Lamp Luminous Flux	Dimmable	Colour Rendering Index
491282 10	HalogenA IDE 1000W E40 230V CL 1CT	T38	Clear	GES	any	230	1000	4.35	24000	yes	100

## Compare table

Order code	Full product name	Life to 50% failures	Lamp Luminous Efficacy	Colour Temperature
491282 10	HalogenA IDE 1000W E40 230V CL 1CT	2000	24	2900



© 2010 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2010, October 20  
data subject to change