



Finish : Reflector

A (1 : 1)

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES 9238 502 32300 0833/000 p.190-1 Of 17/07/2002				HALOGEN LAMP INFRARED INDUSTRIAL 13169X/98 500W 120V REFL						9238 502 32300 0833/000			30/11/2010		
REF. : IRK N 2009-066		DOCUMENTATION		UNIT mm	PROJ. EUROP 	2 SH	SH	190-1	10	1:2	A4				
NAME : J.P. CHARLIER		VALIDATION : A. PICHARD			DR. FISCHER Europe										
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															

PRODUCT REQUIREMENT SHEET

See LV 75-032

MEASURING VOLTAGE	120V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	500W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2450 K 2350 K	± 100 K Indicative value
FLUX (HeLeN lamp)	NA	
WEIGHT	40 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9238 502 32300			01/12/2010				
9238 502 32300		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		13169X/98 500W 120V REFL													
Of 17/07/2002		REF. : IRK N 2009-066		DOCUMENTATION	UNIT mm	PROJ EUROP	2 SH	SH	190-2	10			A4		
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															