

# ITT 700 W 235 V-0170 K R7S

HALOTHERM | Infrared halogen lamps, quartz clear



- Plastics, paper and printing industries
- Drying paint and varnishes
- Coil coating
- Keeping food warm in restaurants

#### **Product benefits**

- Short response time
- High efficiency
- Precise controllability
- Long lamp life



### **Technical data**

#### **Electrical data**

| Nominal wattage      | 700 W  |
|----------------------|--------|
| Nominal voltage      | 235 V  |
| Nominal current      | 3.00 A |
| Lamp current         | 3 A    |
| Construction voltage | 235 V  |
| Construction wattage | 0.7 kW |


### Light technical data

| Color temperature | 2350 K |
|-------------------|--------|

## Dimensions & weight

| Diameter        | 10.0 mm   |
|-----------------|-----------|
| Length          | 250.7 mm  |
| Filament length | 170.00 mm |





Product line drawing

### Lifespan

| Lifespan | 5000 h |
|----------|--------|
|          |        |

### Additional product data

| Base (standard designation) | R7s |
|-----------------------------|-----|

## Capabilities

| Burning position   | p15   |
|--------------------|-------|
| Fuse, quick-acting | 6.3 A |

### Product datasheet





Burning position



# **Logistical Data**

| Product code  | Packaging unit<br>(Pieces/Unit) | Dimensions (height x width x length) | Gross weight | Volume               |
|---------------|---------------------------------|--------------------------------------|--------------|----------------------|
| 4008321203533 | Folding carton box<br>1         | 26 mm x 26 mm x 303<br>mm            | 42.00 g      | 0.20 dm <sup>3</sup> |
| 4008321203540 | Shipping carton box 12          | 117 mm x 95 mm x<br>315 mm           | 492.67 g     | 3.50 dm <sup>3</sup> |

### Product datasheet



| -  |     |     |   |    |
|----|-----|-----|---|----|
| Di | isc | laı | m | er |

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.