

# MASTER LEDspot MV

## MASTER LEDspotMV D 4-35W GU10 WW 25D

Delivering a warm, halogen-like accent beam, MASTER LEDspot MV is a perfect fit for spot lighting (track, corridors, lift lobbies, display cases and cabinets) in the hospitality industry. It is particularly suitable to public areas where the light is on 24/7, such as lobbies, corridors, stairwells. MASTER LEDspot MV delivers huge energy savings and minimizes maintenance cost without any compromise on brightness, enabling hospitality owners to achieve a return on their investment within one year. These LEDspots are compatible with most existing fixtures with a GU10 holder and designed as a retrofit replacement for halogen or incandescent spots. The dimmable versions drive further efficiencies, while helping to create the desired atmosphere. For environments where the right atmosphere needs to be created (e.g. bars and restaurants), the "DimTone" feature could be useful. This is a LED feature that creates a warmer tone once light is dimmed down to lower intensities.

### Product data

#### • General Characteristics

Cap-Base	GU10
Bulb	- [-]
Rated Lifetime	25000 hr
(hours)	

#### • Light Technical Characteristics

Color Code Color Designation	WW Warm White
(text)	25 D
Beam Angle	25 D
Beam Description	- [-]
Correlated Color	2700 K
Temperature	
Luminous Intensity	700 cd
Color rendering	80
index	
Color Temperature	2700 K [CCT 2700K]
Rated Luminous Flux	180 l m
Nated Luminous Hux	

#### • Electrical Characteristics

Wattage	4 W
Wattage Technical	4.0 W
Voltage	230 V
Line Frequency	50-60 Hz
Power Factor	0.6 -
Lamp Current mA	29 mA
Dimmable	Yes

#### 0.5 (max) s Starting Time Measuring Conditions 50000x Switching cycle

35 W

55 mm 50 mm

10

0.035 kg

Wattage Equivalent

# • Product Dimensions

Overall Length C Diameter D

## • Product Data

Order code Full product code Full product name

Order product name Pieces per pack Packing configuration Packs per outerbox

Bar code on pack -

Logistic code(s) -12NC

Net weight per piece

EAN1

Bar code on outerbox - EAN3

929000212602 929000212602 MASTER LEDspotMV D 4-35W GU10 WW 25D MAS LEDspotMV D 4-35W GU10 WW 25D 10 8718291192343 8718291192350 929000212602





## Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)

## Dimensional drawing

#### MASTER LEDspotMV D 4-35W GU10 WW 25D

Product	C (Norm)	C1 (Max)	D (Norm)	D1 (Norm)
LED D 4-35W GU10 WW 25D	55	-	50	-

GU10



 $\textcircled{\mbox{\sc c}}$  2012 Koninklijke Philips Electronics N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting