

MASTER LEDbulb

MASTER LEDbulb D 17-75W E27 WW

The MASTER LEDbulb range delivers a dimmable glow effect for a welcoming, warm atmosphere, making it ideal for general lighting applications in the hospitality industry. Its unique design radiates warm light in all directions, making it a true alternative to the incandescentlamp. They are particularly suitable for public areas such as lobbies, corridors, stairwells, where the light is always on. Compatible with existing fixtures with an E27 holder and designed for retrofit replacement of incandescent bulbs, MASTER LEDbulb delivers huge energy savings and minimizes maintenance cost without any compromise on light quality.They can be used together with most leading-edge dimmers, enabling further efficiencies while helping to create the desired atmosphere.

Product data

General Characteristics

Cap-Base Bulb	E27 A67 [A 67mm]
Rated Lifetime	25000 hr
(hours)	
Rated Lifetime	15 an
(years)	

• Light Technical Characteristics

Color Code	WW
Color Designation	Warm White
(text)	2700 //
Correlated Color	2700 K
Temperature Color rendering	80
index	80
Color Temperature	2700 K [CCT 2700K]
Rated Luminous Flux	1055 Lm

• Electrical Characteristics

Wattage	17 W	
Wattage Technical	17.0 W	
Voltage	230 V	
Line Frequency	50-60 Hz	
Power Factor	0.7 -	
Lamp Current mA	90 mA	
Dimmable	Yes	
Wattage Equivalent	75 W	
Starting Time	0.5 (max)	

s

Energy Efficiency Label (EEL)	Class A
Measuring Conditions Switching cycle	50000×
• Product Dimensions Overall Length C	127.2 mm

61 mm

• Environmental characteristics

• Product Data

Diameter D

Order code Full product code Full product name

Order product name Pieces per pack

Packing configuration

Packs per outerbox

Bar code on pack -

outerbox - EAN3 Logistic code(s) -

EAN1 Bar code on

12NC

929000215502 929000215502 MASTER LEDbulb D 17-75W E27 WW MAS LEDbulb D 17-75W E27 WW 1 6 6 8 718291193463 8718291193470 929000215502

Net weight per piece 0.224 kg






MASTER LEDbulb

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures

with lamp-holders that offer sufficient space (10 mm free air space)

Dimensional drawing



MASTER LED 17-75W E27 2700K 230V A67 DIM

_	Product	C (Norm)	C1 (Max)	D (Norm)	D1 (Norm)
	LED D 17-75W E27 WW	127.2	-	61	-





 $\textcircled{\mbox{\sc c}}$ 2013 Koninklijke Philips Electronics N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

• Not intended for use with emergency light fixtures or exit lights