

Novallure 2W E14 3000K P45 CL ICT

Product family description

Delivering incandescent-like sparkling light effects, Novallure LED candle and luster bulbs are ideal for general and decorative lighting in the hospitality industry, as well as in home environments.

Mounted in full view in chandeliers, wall scones or modern luminaires, the clear or frosted glass bulbs fit all existing fixtures with an E14 socket. Drawing upon inputs from chandelier makers and designed to enhance the aesthetic appeal of the chandelier or luminaire, not only when lit but also when not, these lamps come in a classical slender shape with a unique, eye-catching lens design. They produce a beautiful sparkling warm light that delivers huge energy savings and minimises maintenance cost.

Product Features

- · Unique eye-catching lens design
- Inviting, sparkling light effect
- Lower maintenance cost due to 15 times longer lifetime
- · Free of mercury and hazardous materials.
- · available in clear and frosted

Product Benefits

- Sparkling warm light
- 80% energy saving
- Classical slender shape and crystal-clear bulb, fitting all existing fixtures with E14 holders – enhances original design concept of chandelier

Application

- Hospitality applications and in the home
- · Chandelier, wall scone or modern luminaire

Product data
Order code 852912 00



roduct name Normal Norm		
roduct name Nor product name Nor per pack I nor configuration I nor per outerbox I nor per outerbox I nor per outerbox Nor pe	Novallu. 2W E14 3000K P45 CL 1CT/10	
r product name Ing type Is per pack Ing configuration Ing configuration Ing per outerbox Ing de on pack - EAN1 Ing de on intermediate packing - EAN2 Ing ode on outerbox - EAN3 In code(s) - I2NC	Novallu. 2W E14 3000K P45 CL 1CT/10	
ng type s per pack ng configuration per outerbox ode on pack - EAN1 ode on intermediate packing - EAN2 ode on outerbox - EAN3 ic code(s) - I2NC		
s per pack I ng configuration I0 per outerbox I0 per on pack - EAN I 87 pode on intermediate packing - EAN 2 pode on outerbox - EAN 3 87 ic code(s) - I2NC		
ng configuration 10 per outerbox 10 ode on pack - EAN 1 87 ode on intermediate packing - EAN 2 ode on outerbox - EAN 3 87 ic code(s) - 12NC		
per outerbox 10 ode on pack - EAN1 87 ode on intermediate packing - EAN2 ode on outerbox - EAN3 87 ic code(s) - 12NC		
ode on pack - EAN I 87 ode on intermediate packing - EAN2 ode on outerbox - EAN3 87 cic code(s) - I2NC	0	
ode on intermediate packing - EAN2 ode on outerbox - EAN3 sic code(s) - 12NC	0	
ode on outerbox - EAN3 87 ic code(s) - I2NC	727900852912	
ic code(s) - I2NC		
	727900852929	
S code		
veight per piece 0.0	0.035 KG	
ssor order code		
Sase	ES	
P4	P45 [P 45mm]	
inish	Clear	
ge Lifetime 15	5000 hr	
age 2V	W	
ge 23	30-240V	
ır Code W	VH .	
r Designation W	Vhite	
ous Flux 50	0 Lm	
r rendering index 80	30	
ous Efficacy Lamp 25		
r Temperature 30	25 Lm/W	




Novallu. E14 P45 CL


no image available

Novallure B35 E14





Novallu. 2W E14/WH 230-240V



Novallu. E14 P45

	С	D
Full product name	Nom	Nom
Novallure 2W E14 3000K P45 CL ICT	77	45



$\hbox{$\mathbb{C}$2009 Koninklijke Philips Electronics N.V.}$

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liablity will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Document order number : 0000 000 00000