



MASTERLine ES

MASTERLine ES 35W GU5.3 12V 8D 1CT

MASTER dichroic coated low-voltage halogen reflector lamp with EcoBoost technology: the most energy-efficient dichroic lamp on the market

Product data

• General Characteristics

Philips Code	18138
ANSI Code Halogen	na [-]
Cap-Base	GU5.3
Bulb	MR16 [MR 16inch/50mm]
Operating Position	any [Any or Universal (U)]
Life to 50% failures	5000 hr

• Electrical Characteristics

Lamp Wattage	35 W
Lamp Wattage Technical	35 W
Voltage	12 V
Lamp Current	2.92 A
Dimmable	Yes

• Light Technical Characteristics

Beam Angle	8 D
Beam Angle Technical	8 D
Luminous Intensity	13500 (max) cd
Color Rendering Index	100 Ra8
Color Temperature	3000 K
Color Temperature Technical	3000 K

• Product Dimensions

Overall Length C	50.5 (max) mm
------------------	---------------

Overall Length Rim C1	50.5 (max) mm
Diameter D	51 (max) mm

• Luminaire Design Requirements

Cap-Base Temperature	380 (max) C
Bulb Temperature	380 (max) C

• Product Data

Order code	924895517101
Full product code	924895517101
Full product name	MASTERLine ES 35W GU5.3 12V 8D 1CT
Order product name	MASTERL ES 35W GU5.3 12V 8D 1CT/4X5F
Pieces per pack	1
Packing configuration	4X5F
Packs per outerbox	20
Bar code on pack - EAN1	8711500413871
Bar code on intermediate packing - EAN2	8711500413918
Bar code on outerbox - EAN3	8711500410139
Logistic code(s) - 12NC	924895517101
ILCOS code	HRGS-35-12-GU5.3-50/8
Net weight per piece	30.000 gr





asimpleswitch.com

PHILIPS

sense and simplicity

Dimensional drawing



Product	C1 (Max)	D (Max)
MLES 18138 35W GU5.3 12V MR16 8D	50.5	51



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, May 14
data subject to change