

Mini-Lynx R50 reflector 5W E14

R50 REFL 5W/E14 827 SLV

0031120



Range features

- ML R50 REFL 5W E14 827 BLSTR



PRODUCT OVERVIEW

Ordering number	0031120
Light colour	827 Homelight
Technology	Compact Fluorescent
Average life (Rated) (h)	10000
Lamp finish	827 / Homelight Deluxe
Lamp shape	Reflector
Dimmable	No
Cap/Base	E14
Type	Mini-Lynx R50
EAN code	54 10288311203
CRI (Ra)	80
Beam angle(°)	80% cd <120
Colour temperature (K)	2700
Useful luminous flux (Rated) (lm)	165
Watt (Nominal) (W)	5.0
Equivalent watt (W)	n/a (classified as a reflector)
Voltage (V)	230-240

Mini-Lynx R50 reflector 5W E14

R50 REFL 5W/E14 827 SLV

0031120

DATA TABLE

General data

Ordering number	0031120
Technology	Compact Fluorescent
Dry applications use only	Yes
Energy saving lamp	0.8
Average life (Rated) (h)	10000
Average life (Nominal) (h)	10000
Lamp finish	827 / Homelight Deluxe
Lamp shape	Reflector
Dimmable	No
Cap/Base	E14
Type	Mini-Lynx R50
EAN code	54 10288311203
E-number FI	4940142
Long description	ML R50 REFL 5W E14 827 BLSTR
Product name	R50 REFL 5W/E14 827 SLV
Lamp mercury content (mg)	<3.5
Starting time (max) (s)	< 2.0
Warm-up time to 60% of full light (max) (s)	< 60 s
Control gear required	No
Burning position	Universal
IEC Reference	IEC 60968
IEC Reference 2	IEC 60969
IEC Reference 3	IEC 55015
ILCOS code	FBRH-5/27/1b-E14-50/85
Intended purpose	General lighting
No. of switching cycles before premature failure (min)	6000
Special purpose lamp	No
Transformer required	No
Sales pack quantity	10
Optimal operating condition (°C)	25° C, cap-up, Stated lumen output may vary if ope

Mini-Lynx R50 reflector 5W E14

R50 REFL 5W/E14 827 SLV

0031120

Optical data

Light colour	827 Homelight
CRI (Ra)	80
Beam angle (°)	80% cd <120
Colour temperature (K)	2700
Lumen maintenance at end of nominal life (%)	80
Useful luminous flux (Rated) (lm)	165
Luminous flux (Nominal) (lm)	165
Chromaticity coordinate Y	0.42
Chromaticity coordinate X	0.463

Electrical data

Watt (Nominal) (W)	5.0
Equivalent watt (W)	n/a (classified as a reflector)
Watt (Rated) (W)	5.0
Voltage (V)	230-240
Current (A)	0.04
Lamp power factor	> 0.5

Physical data

Weight (kg)	0.04
Lamp Length (mm) - C/L	85
Lamp Diameter (mm) - D	50

Mini-Lynx R50 reflector 5W E14

R50 REFL 5W/E14 827 SLV

0031120

TECHNICAL DRAWINGS

