

Halogenlamps with high temperature - resistant pins




Fig. 1




Fig. 2

Description

Halogen lamps with high temperature - resistant pins
base: G6,35-15 and * GY6,35-15

Application

Halogen lamps for customer specific application

Technical data

Typ-No.	Type	Rated voltage V	Power		Luminous flux		Life average h	Operating positions	Fig.
			rated W	max. W	rated lm	min. lm			
molybdenum									
55179	HLWS	22,8	40	44,8	900	792	800	s90	2
55180	HLL	22,8	40	44,8	700	616	1000	s90	2
55181	HLL	22,8	40	44,0	800	680	1000	s90	1
55240 *	HLL	22,8	50	56,0	1100	935	2000	s90	2
55241	HLL	22,8	50	55,0	950	808	1000	s90	1
55244 *	HLL	24	50	55,0	850	840	2000	s90	1
55248 *	HLL	24	75	82,5	1500	1275	2000	s90	2
55350 *	HLL	24	100	110,0	2000	1760	2000	s90	1
platinized									
55941	HLWS4	24	150	168,0	5000	4400	50	s90	1
55943	HLWS4	24	150	168,0	5000	4400	300	s90	1
55952	HLP4	24	250	275,0	8400	7392	300	s90	1

Ordering data

Type	Packing quantity			Ordering-No.
	Industrial	Trade	Blister	
55179	900	-	-	55179
55180	900	100	-	55180
55181	900	100	-	55181
55240	900	100	-	55240
55241	900	100	-	55241
55244	-	100	-	55244
55248	900	-	-	55248
55350	900	-	-	55350
55941	-	100	-	55941
55943	-	100	-	55943
55952	-	100	-	55952