



Energy saving for professionals. OSRAM DULUX® EL LONGLIFE & GLOBE and OSRAM DULUX® EL LONGLIFE intelligent energy-saving lamps 15,000 hour¹ average life – 500,000 switching cycles.

Type Reference	Fig. no.	Product number (EAN-Code)	Wattage	Base	Luminous flux	Color rendering group	Length	Diameter	Weight	Light color
OSRAM DULUX® EL LONGLIFE & GLOBE										
OSRAM DULUX EL LONGLIFE	1	4050300502953	3 W	E14	100 lm	1B	115 ±3 mm	30 mm	40 g	827
OSRAM DULUX EL LONGLIFE	2	4050300314747	5 W	E14	240 lm	1B	119 ±3 mm	36 mm	42 g	827
OSRAM DULUX EL LONGLIFE	3	4050300357430	5 W	E27/B22d	240 lm	1B	113 ±3 mm	36 mm	42 g	827
OSRAM DULUX EL LONGLIFE	2	4050300315157	7 W	E14	400 lm	1B	119 ±3 mm	36 mm	42 g	827
OSRAM DULUX EL LONGLIFE	3	4050300288819	7 W	E27/B22d	400 lm	1B	113 ±3 mm	36 mm	42 g	827
OSRAM DULUX EL LONGLIFE	3	4050300292373	7 W	E27	400 lm	1B	113 ±3 mm	36 mm	42 g	840
OSRAM DULUX EL LONGLIFE	4	4050300811451	11 W	E14	660 lm	1B	126 ±3 mm	45 mm	62 g	827
OSRAM DULUX EL LONGLIFE	5	4050300811598	11 W	E27/B22d	660 lm	1B	117 ±3 mm	45 mm	62 g	827
OSRAM DULUX EL LONGLIFE	5	4050300811727	11 W	E27/B22d	660 lm	1B	117 ±3 mm	45 mm	62 g	840
OSRAM DULUX EL LONGLIFE	5	4050300811789	11 W	E27/B22d	630 lm	1B	117 ±3 mm	45 mm	62 g	860
OSRAM DULUX EL LONGLIFE	5	4050300811635	15 W	E27/B22d	900 lm	1B	128 ±3 mm	45 mm	65 g	827
OSRAM DULUX EL LONGLIFE	5	4050300811741	15 W	E27	900 lm	1B	128 ±3 mm	45 mm	65 g	840
OSRAM DULUX EL LONGLIFE	5	4050300811802	15 W	E27/B22d	855 lm	1B	128 ±3 mm	45 mm	65 g	860
OSRAM DULUX EL LONGLIFE	5	4050300811673	20 W	E27/B22d	1230 lm	1B	145 ±3 mm	45 mm	73 g	827
OSRAM DULUX EL LONGLIFE	5	4050300811765	20 W	E27	1230 lm	1B	145 ±3 mm	45 mm	73 g	840
OSRAM DULUX EL LONGLIFE	5	4050300811826	20 W	E27/B22d	1170 lm	1B	145 ±3 mm	45 mm	73 g	860
OSRAM DULUX EL LONGLIFE	6	4050300028965	23 W	E27/B22d	1500 lm	1B	173 ±3 mm	52 mm	100 g	827
NEW OSRAM DULUX EL LONGLIFE	6	4050300326429	23 W	E27	1500 lm	1B	173 ±3 mm	52 mm	100 g	840
NEW OSRAM DULUX EL LONGLIFE	6	4050300421605	23 W	E27/B22d	1440 lm	1B	173 ±3 mm	52 mm	100 g	860
OSRAM DULUX EL LONGLIFE GLOBE	9	4050300276175	15 W	E27/B22d	800 lm	1B	167 ±3 mm	120 mm	150 g	827
NEW OSRAM DULUX EL LONGLIFE GLOBE	9	4050300276274	20 W	E27/B22d	1100 lm	1B	167 ±3 mm	120 mm	155 g	827
NEW OSRAM DULUX® EL LONGLIFE intelligent energy-saving lamps										
OSRAM DULUX EL FACILITY ^{2*}	4	4050300938295	10 W	E14	530 lm	1B	126 ±3 mm	45 mm	63 g	827
NEW OSRAM DULUX EL FACILITY ^{2*}	5	4050300938257	10 W	E27/B22d	530 lm	1B	117 ±3 mm	45 mm	68 g	827
NEW OSRAM DULUX EL FACILITY ^{2*}	5	4050300631905	14 W	E27/B22d	800 lm	1B	123 ±3 mm	45 mm	70 g	827
NEW OSRAM DULUX EL FACILITY ^{2*}	5	4008321118356	18 W	E27/B22d	1100 lm	1B	137 ±3 mm	45 mm	72 g	827
OSRAM DULUX EL SENSOR	5	4008321102300	11 W	E27	660 lm	1B	120 ±3 mm	45 mm	70 g	827
NEW OSRAM DULUX EL SENSOR	5	4008321451299	15 W	E27/B22d	900 lm	1B	129 ±3 mm	45 mm	77 g	827
OSRAM DULUX EL CONCENTRA R80	10	4008321067401	23 W	E27/B22d	500 cd	1B	125 ±3 mm	80 mm	190 g	827
OSRAM DULUX EL LL CLASSIC A	11	in preparation ⁵	20 W	E27	1250 lm	1B	135 ±3 mm	60 mm	121 g	827
OSRAM DULUX EL REFLECTOR	7	4050300306094	15 W	E27	335 cd	1B	143 ±3 mm	102 mm	145 g	827
NEW OSRAM DULUX EL REFLECTOR	7	4050300291703	20 W	E27	450 cd	1B	161 ±3 mm	117.5 mm	170 g	827
NEW OSRAM DULUX EL REFLECTOR	7	4050300857725	20 W	E27	450 cd	1B	161 ±3 mm	117.5 mm	170 g	840
OSRAM DULUX EL DIM ³	6	4008321080370	20 W	E27/B22d	1230 lm	1B	158 ±3 mm	58 mm	110 g	827
NEW OSRAM DULUX EL VARIO	5	4008321132727	20/8 W	E27/B22d	1230/250 lm	1B	145 ±3 mm	45 mm	79 g	827
OSRAM CIRCOLUX EL	4	4050300626628	24 W	E27	1700 lm	1B	99 ±3 mm	225 mm	170 g	827
OSRAM DULUX EL SOLAR 12 V DC VARIO ^{4*}	4	4008321118417	11/6 W	E27	600/270 lm	1B	127 ±3 mm	45 mm	75 g	827
OSRAM DULUX EL SOLAR 12 V DC ⁴	4	4008321118370	11 W	E27	600 lm	1B	127 ±3 mm	45 mm	75 g	827

¹ Switching cycle 90 min on, 15 min off

² Can be used for dc applications without restrictions and in emergency systems (176 to 310 V)

³ Can be used in all applications with suitable leading-edge phase dimmers

⁴ 10,000 hour average life (switching cycle 60 min on, 15 min off)

* Switching cycle unlimited

⁵ Available from September 2007