


















Produkt- bezeichnung	Produkt- nummer	W	V		cd				t [h]		
HALOSPOT® 111, Aluminium-Reflektor, Ø 111 mm, Niederdrucktechnik											
41830SSP	4050300011141	35	6	4	30000	111	67	51	3000	G53 ¹⁾	6
41832SSP	4050300335728	35	12	4	35000	111	67	51	3000	G53 ¹⁾	6
41832FL	4050300335766	35	12	24	2500	111	67	51	3000	G53 ¹⁾	6
41835SSP	4050300011165	50	12	4	40000	111	67	51	3000	G53 ¹⁾	6
41835SP	4050300011752	50	12	8	20000	111	67	51	3000	G53 ¹⁾	6
41835FL	4050300011769	50	12	24	4000	111	67	51	3000	G53 ¹⁾	6
41835WFL	4008321909213	50	12	45	1400	111	67	51	3000	G53 ¹⁾	6
41840SP	4050300011776	75	12	8	30000	111	67	51	3000	G53 ¹⁾	6
41840FL	4050300011783	75	12	24	5300	111	67	51	3000	G53 ¹⁾	6
41840WFL	4050300011790	75	12	45	2000	111	67	51	3000	G53 ¹⁾	6
41850SP	4050300358604	100	12	8	48000	111	67	51	3000	G53 ¹⁾	6
41850FL	4050300358628	100	12	24	8500	111	67	51	3000	G53 ¹⁾	6
41850WFL	4050300358642	100	12	45	2800	111	67	51	3000	G53 ¹⁾	6



Produkt- bezeichnung	Produkt- nummer	W	V	lm				t [h]			
HALOSTAR STARLITE® Niedervolt-Stiftsockellampen, Niederdrucktechnik											
64405S ²⁾	4050300335032		5	12	60	22	9,5	33	4000	G4	40
64410S	4050300335131		10	6	110	22	9,5	33	4000	G4	40
64415S	4050300335087		10	12	130	22	9,5	33	4000	G4	40
64425S	4050300335162		20	12	320	22	9,5	33	4000	G4	40
64427S	4050300328171		20	12	320	30	12	44	4000	GY6,35	40
64432S	4050300017426		35	12	600	30	12	44	4000	GY6,35	40
64440S	4050300328201		50	12	910	30	12	44	4000	GY6,35	40
64450S	4050300490151		75	12	1450	30	12	44	4000	GY6,35	40
64458S	4050300490182		90	12	1800	30	12	44	4000	GY6,35	40



Produkt- bezeichnung	Produkt- nummer	W	V	lm				t [h]			
HALOSTAR® STANDARD Niedervolt-Stiftsockellampen, Niederdrucktechnik											
klar											
64415	4050300010717		10	12	140	22	9,5	33	2000	G4	40
64425	4050300003924		20	12	320	22	9,5	33	2000	G4	40
64432	4050300364629		35	12	600	30	12	44	2000	GY6,35	40
64440	4050300324432		50	12	910	30	12	44	2000	GY6,35	40
mattiert											
64415F	4050300269047		10	12	130	22	9,5	33	2000	G4	40
64425F	4050300324388		20	12	300	22	9,5	33	2000	G4	40
64432F	4050300277332		35	12	570	30	12	44	2000	GY6,35	40
64440F	4050300325170		50	12	830	30	12	44	2000	GY6,35	40



1) Bei Verwendung von Anschlusselementen ist zusätzlich eine Halterung am Reflektorrand erforderlich
 2) Lampe in Hartglasausführung mit Querwendel