



product details

64465 150W 24V GY6,35 FS1



Product description: 64465 150W 24V GY6,35 FS1
 Product code: 4050300335698
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300335698

Applications	
Dimmable	Yes
Burning position	any

Categorizations	
SEG number	8326616
ILCOS	HSGT/C/UB-150-24-GY6,35-16/32

General Description	
Base (standard designation)	GY6.35
Filament setting	Axial
Mercury-free	Yes
Rated lamp mercury content	0.0 mg

Technical - Electrical Data	
Nominal wattage (packaging)	150 W
Construction wattage	150 W
Nominal voltage	24 V
Rated number of switching cycles	1000000 ¹⁾
Rated power factor λ	1.00

Technical - Geometries	
Overall length	44.00 mm
Contact spacing	6.35 mm
Diameter	12 mm
Length	44.00 mm
Light center length (LCL)	32 mm

Technical - Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h

Technical - Light Technical Data	
Rated color rendering index Ra	100
Luminous flux	3200 lm
Nominal luminous flux	3200 lm
Rated luminous flux	3200 lm
Lumen main.fact.at end of nom.life time	0.80
Color temperature	3000 K
Rated color temperature	3000 K
Color rendering index Ra	100
Rated warm-up time (60 %)	0 s
Rated starting time	0.0 s



product details

64465 150W 24V GY6,35 FS1

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300335698	Folding carton box contains 1 Piece	25,000 mm x 23,000 mm x 70,000 mm	7,000 g (0,000 g)	0,040 Cubic dec.
4050300942438	Shipping carton box contains 40 Piece	121,000 mm x 107,000 mm x 144,000 mm	321,000 g (0,000 g)	1,864 Cubic dec.

HALOSTAR 24 V

UV-reducing quartz suppresses unwanted UV radiation. Complies with the UV protection thresholds of IEC 60432-3.

- The base pins are tempered to protect against corrosion
- The axial filament ensures optimum directional light
- High illuminance level

¹⁾ At 1 s on / 1 s off