

HPL 93728 575 W 230 V

HPL | High-performance lamps



Product benefits

Arrangement of filament segments matched to ETC's "Source Four" spotlight family

 $\boldsymbol{\cdot}$ Optimum use of the generated light

 \cdot Same useful luminous flux for which 1,000 W lamps had previously been required



Product datasheet

Technical data


Electrical data


Nominal wattage	575 W
Nominal voltage	230 V

Light technical data

Luminous flux	14900 lm
Color temperature	3200 К

Dimensions & weight









Product line drawing

Base

Base

Diameter	19.0 mm	
Length with base excl. base pins/connection	98.00 mm	
Light center length (LCL)	60.3 mm	
Illuminated field	9.5*11.5 mm ^{2 1)}	
Length	104.0 mm	

¹⁾ Type of filament 6-C8

Lifespan

Lifespan 400 h	
----------------	--

Additional product data

Base (standard designation)	2 pins
Picto Studio	Yes

Capabilities

Product datasheet

Burning position	hs30
Certificates & standards	
EEI – Energy Label	В
Country specific categorizations	
Order reference	93728

Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4050300461816	OSRH93728	-	4736185	-

Product datasheet



Burning position

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4050300461816	HPL 93728 575 W 230 V	Folding carton box 1	42 mm x 42 mm x 131 mm	0.23 dm³	68.50 g
4050300461823	HPL 93728 575 W 230 V	Shipping carton box 12	145 mm x 133 mm x 174 mm	3.36 dm ³	947.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.