

HPL 93729 LL 750 W 230 V

HPL | High-performance lamps



Product benefits

- Arrangement of filament segments matched to ETC's "Source Four" spotlight family
- Optimum use of the generated light
- Same useful luminous flux for which 1,000 W lamps had previously been required



Product datasheet

Technical data




Electrical data

Nominal wattage	750 W
Nominal voltage	230 V

Light technical data

Nominal luminous flux	15600 lm
Luminous flux	15600 lm
Color temperature	3050 K

Dimensions & weight



Product line drawing

Base

Base

Diameter	19.0 mm
Length with base excl. base pins/connection	104.00 mm
Light center length (LCL)	60.3 mm
Illuminated field	15.5*11.0 mm ² ¹⁾
Length	104.0 mm

¹⁾ Type of filament 6-C8

Lifespan

Lifespan	1500 h
----------	--------

Additional product data

Base (standard designation)	2 pins
Picto Studio	Yes

Product datasheet

Capabilities

Burning position	hs30
------------------	------

Certificates & standards

EEL – Energy Label	C
--------------------	---


Country specific categorizations

Order reference	93729 LL
-----------------	----------

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321090324	OSRHPL93729LL	-	-	-

Product datasheet



Burning position

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4008321090324	HPL 93729 LL 750 W 230 V	Folding carton box 1	42 mm x 42 mm x 131 mm	0.23 dm ³	76.67 g
4008321090331	HPL 93729 LL 750 W 230 V	Shipping carton box 12	145 mm x 148 mm x 174 mm	3.73 dm ³	953.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.