

PAR 36

PAR 36 120V 650W

0060503



- Features
- Pressed glass reflector lamps
- Beam patterns: from very narrow spot through wide angle floods
- Consistency from lamp to lamp
- Economical light source for effects
- Halogen version delivers maintained beam intensity throughout life
- Applications
- Entertainment and Architectural applications
- Displays
- Museums
- Exhibitions
- Gardens
- Discos
- Directions for use
- Easy handling
- Can be used with very economical fixtures (PAR cans)

PRODUCT OVERVIEW

Ordering number	0060503
EAN code	5410288605036
Colour temperature (K)	3200
Nominal average life (h)	100
Cap/Base	Screw Terminal
Lamp Diameter (mm) - D	114
Watt (W)	650
Type	PAR 36
Lamp Length (mm) - C	70
Voltage (V)	120

PAR 36

PAR 36 120V 650W

0060503

DATA TABLE

General data

Ordering number	0060503
Nominal average life (h)	100
Ballast required	
EAN code	5410288605036
IEC Reference	
IEC Reference 2	
IEC Reference 3	
Cap/Base	Screw Terminal
Type	PAR 36
Transformer required	
Unit case	12
Product name	PAR 36 120V 650W
Average rated life (h)	100
Burning position	H15
Long description	Features Pressed glass reflector lamps Beam patterns: from very narrow spot through wide angle floods Consistency from lamp to lamp Economical light source for effects Halogen version delivers maintained beam intensity throughout life Applications Entertainment and Architectural applications Displays Museums Exhibitions Gardens Discos Directions for use Easy handling Can be used with very economical fixtures (PAR cans)

Optical data

Colour temperature (K)	3200
Peak intensity (cd)	24000

Electrical data

Watt (W)	650
Rated watt (W)	650
Voltage (V)	120

PAR 36

PAR 36 120V 650W

0060503

Physical data

Packaging outer height (cm)	21
Packaging single height (cm)	10
Lamp Diameter (mm) - D	114
Lamp Length (mm) - C	70
Packaging outer length (cm)	30
Packaging single length (cm)	10
Packaging outer width (cm)	21
Packaging single width (cm)	10



PAR 36

PAR 36 120V 650W

0060503

TECHNICAL DRAWINGS

