



# PL-S Blacklight Blue

PL-S 9W BLB/2P 1CT

Low-pressure mercury vapour fluorescent lamps with an inner envelope coated with a fluorescent powder emitting long wave UV radiation to excite luminescence

## Product data

### • General Characteristics

Cap-Base	G23
Cap-Base Information	2 Pins
Bulb	2xT12
Bulb Finish	-
Execution	2 Pins
Main Application	Blacklight Blue
Useful Life	3000 hr

### • Electrical Characteristics

Lamp Wattage	9 W
Lamp Wattage Technical	8.6 W
Lamp Voltage	60 V
Lamp Current	0.17 A

### • Light Technical Characteristics

Color Code	108 [08 lead free glass]
Color Designation (text)	Blacklight Blue
Depreciation 5000 hours	30 %
Depreciation 2000 hours	20 %

### • UV-related Characteristics

UV-B/UV-A (IEC)	0.2 %
-----------------	-------

### • Product Dimensions

Base Face to Base Face A	129 (max) mm
Insertion Length B	145 (max) mm
Overall Length C	167.5 (max) mm
Diameter D	28 (max) mm
Diameter D1	13 (max) mm




### • Product Data

Order code	927901710807
Full product code	927901710807
Full product name	PL-S 9W BLB/2P 1CT
Order product name	PL-S 9W BLB/2P 1CT/6X10BOX
Pieces per pack	1
Packing configuration	6X10CC
Packs per outerbox	60
Bar code on pack - EAN1	8711500950901
Bar code on intermediate packing - EAN2	8711500950918
Bar code on outerbox - EAN3	8711500950925
Logistic code(s) - 12NC	927901710807
Net weight per piece	33.700 gr

# PHILIPS

sense and simplicity

## Dimensional drawing



## PL-S

Product	A (Max)	B (Max)	C (Max)	D (Max)	D1 (Max)
PL-S 9W/108/2P	129	145	167.5	28	13



© 2011 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2011, May 16  
data subject to change