



TL-E Circular Standard Colours

TL-E Circular 22W/33-640 1CT

Low-pressure mercury discharge lamps with a circular 29 mm tube
Product Description Low-pressure mercury discharge lamps with a circular 26 mm tube

Product data

• Product Data

Order code	559425 15
Full product code	871150055942515
Full product name	TL-E Circular 22W/33-640 1CT
Order product name	TL-E Circular 22W/33-640 1CT/12
Pieces per pack	1
Packing configuration	12
Packs per outerbox	12
Bar code on pack - EAN1	8711500559425
Bar code on outerbox - EAN3	8711500559326
Logistic code(s) - 12NC	928026203360
ILCOS code	FSC-22/41/2B-E-G10q-29/210
Net weight per piece	0.110 kg

• General Characteristics

Cap-Base	G10q
Bulb	C-T9 [C-T 29 mm]
Life to 50% failures EM	9000 hr

• Electrical Characteristics

Lamp Wattage	22 W
Lamp Wattage EM	22.0 W
Lamp Voltage	62 V
Lamp Current EM	0.400 A
Dimmable	yes

• Environmental Characteristics

Energy Efficiency Label (EEL)	B
-------------------------------	---

Mercury (Hg) Content	30 mg
----------------------	-------


• Light Technical Characteristics

Colour Code	33-640
Colour Rendering Index	63 Ra8
Colour Designation	Cool White
Colour Temperature	4100 K
Chromaticity Coordinate X	377 -
Chromaticity Coordinate Y	381 -
Lamp Luminous Flux EM	1250 Lm
Lamp Luminous Efficacy EM	57 Lm/W
Lumen Maintenance 2000h	85 %
Lumen Maintenance 5000h	81 %
Lumen Maintenance 10000h	73 %
Lumen Maintenance 15000h	69 %
Average Luminance EM	0.85 cd/cm ²

• Product Dimensions

Diameter D	27.1 (min), 30.9 (max) mm
Overall Width E	203.2 (min), 215.9 (max) mm
Inner Width I	147.6 (min), 157.2 (max) mm

Dimensional drawing



Product	D (Min)	D (Max)	E (Min)	E (Max)	I (Min)	I (Max)
TL-E 22W/33-640	27.1	30.9	203.2	215.9	147.6	157.2



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, February 9
data subject to change