



# TL-X XL

TL-X XL 15W/33-640 1SL

Single-pin low-pressure mercury discharge lamps with a tubular 38 mm envelope

## Product data

### • Product Data

Order code	261335 40
Full product code	871150026133540
Full product name	TL-X XL 15W/33-640 1SL
Order product name	TL-X XL 15W/33-640 1SL/25
Pieces per pack	1
Packing configuration	25
Packs per outerbox	25
Bar code on pack - EAN1	8711500261335
Bar code on outerbox - EAN3	8711500261342
Logistic code(s) - 12NC	928037203332
ILCOS code	FD-15/41/2B-LC/N-Fa6
Net weight per piece	109.000 gr

### • General Characteristics

Cap-Base	Fa6
Bulb	T12 [38 mm]
Life to 50% failures EM	26000 hr
Life to 10% failures EM	21000 hr

### • Electrical Characteristics

Lamp Wattage	15 W
Lamp Wattage EM	15.0 W
Lamp Voltage	44 V
Lamp Current EM	0.370 A
Dimmable	yes

### • Environmental Characteristics

Energy Efficiency Label (EEL)	B
Mercury (Hg) Content	8.0 mg

### • Light Technical Characteristics


Colour Code	33-640
Colour Rendering Index	63 Ra8
Colour Designation	Cool White
Colour Temperature	4100 K
Chromaticity Coordinate X	377 -
Chromaticity Coordinate Y	381 -
Lamp Luminous Flux EM	665 Lm
Lamp Luminous Efficacy EM	44 Lm/W
Lumen Maintenance 2000h	88 %
Lumen Maintenance 5000h	83 %
Average Luminance EM	0.54 cd/cm <sup>2</sup>

### • Product Dimensions

Base Face to Base Face A	421.5 mm
Insertion Length B	436.5 (min), 440 (max) mm
Overall Length C	458.5 mm
Diameter D	40.5 mm

**PHILIPS**  
sense and simplicity

## Dimensional drawing



Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL-X XL 15W/33-640	421.5	436.5	440	458.5	40.5



© 2011 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2011, February 9  
data subject to change