



# Primaline Halogen Transformers

Primaline 105 230-240V 50/60Hz

High-Frequency electronic transformer for operation with 12 V halogen lamps, available in 70, 105 and 150 W versions

## Product data

### • General Characteristics

Rated Number of Lamps	2 piece
Rated Ballast-Lamp Power	50-105
Rated Lamptype	LV Halogen
Line Voltage	230-240 V
Line Frequency	50/60 Hz
Lifetime 90% surv.@Tcaselife	50000 hr

### • Operating Characteristics

Power Consumption Range	35-105 W
Ballast Efficiency Factor	0.95 -

### • Temperature Characteristics

T-case life	65 C
T-case maximum	80 (max) C

### • Approval & Application Chars

Approval marks	ENEC / SELV
----------------	-------------

CE marking Yes




### • Product Dimensions

Length A1	110 mm
Width B1	45 mm
Height C1	33 mm

### • Product Data

Order code	913700627691
Full product code	913700627691
Full product name	Primaline 105 230-240V 50/60Hz
Order product name	Primaline 105 230-240V 50/60Hz
Pieces per pack	1
Packing configuration	50
Packs per outerbox	50
Bar code on pack - EAN1	8711500912688
Bar code on outerbox - EAN3	8711500912695
Logistic code(s) - 12NC	913700627691
Net weight per piece	0.126 kg

## Dimensional drawing



Product	A1 (Norm)	B1 (Norm)	C1 (Norm)
Primaline 105 230-240V 50/60Hz	110	45	33



© 2011 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2011, May 14  
data subject to change