

## PureBronze Suntanning - High Pressure HID

PureBronze PBF 250W SE

**0024250**



### Range features

- Features
- Short irradiation and exposure times
- Ozone free construction
- Long-life types offer outstanding UV-A maintenance out to 800 hours
- Special versions available upon request
- Complete PBF range also available
- 
- Applications
- Domestic cosmetic facial tanning
- Professional facial, half body and full body units
- Short intense tanning sessions
- 
- Directions For Use
- Only use in tanning devices equipped with appropriate filter and timer
- Burning position: horizontal  $\pm 10^\circ$  for double ended types : universal for single ended types
- Do not touch the quartz envelope with bare fingers
- Pinch temperature: max 350°C
- Bulb temperature: min 750°C, max 950°C



### PRODUCT OVERVIEW

Ordering number	0024250
Average life (Rated) (h)	600
EAN code	5410288242507
Watt (Nominal) (W)	250

## PureBronze Suntanning - High Pressure HID

PureBronze PBF 250W SE

**0024250**

### DATA TABLE

#### General data

<b>Ordering number</b>	0024250
<b>Average life (Rated) (h)</b>	600
<b>EAN code</b>	5410288242507
<b>Long description</b>	Features . Short irradiation and exposure times . Ozone free construction . Long-life types offer outstanding UV-A maintenance out to 800 hours . Special versions available upon request . Complete PBF range also available . . Applications . Domestic cosmetic facial tanning . Professional facial, half body and full body units . Short intense tanning sessions . . Directions For Use . Only use in tanning devices equipped with appropriate filter and timer . Burning position: horizontal $\pm 10^\circ$ for double ended types : universal for single ended types . Do not touch the quartz envelope with bare fingers . Pinch temperature: max 350°C . Bulb temperature: min 750°C, max 950°C
<b>Product name</b>	PureBronze PBF 250W SE
<b>Lamp mercury content (mg)</b>	12
<b>Sales pack quantity</b>	10

#### Electrical data

<b>Watt (Nominal) (W)</b>	250
---------------------------	-----

#### Physical data

<b>Weight (kg)</b>	0.02
<b>Single packaging type</b>	Box/Sleeve
<b>Single package dimensions (L x W x H) (cm)</b>	17.00 x 4.50 x 4.50
<b>Inner package dimensions (L x W x H) (cm)</b>	23.00 x 18.00 x 10.00
<b>Inner package net weight (kg)</b>	0.18
<b>Outer package dimensions (L x W x H) (cm)</b>	51.00 x 24.50 x 19.00