

## PureBronze Suntanning - High Pressure HID

PureBronze PBO 1000W C 400 V

**0024221**



- Features
- Short irradiation and exposure times
- Ozone free construction
- Long-life types offer outstanding UV-A maintenance out to 1000 hours
- Built according to DIN-EN-ISO 9001
- Special versions available upon request
- Complete PBF range also available
- 
- Applications
- Domestic cosmetic facial tanning
- Professional facial, half body and full body units
- Short intense tanning sessions
- 
- DIRECTIONS FOR USE
- Only use in tanning devices equipped with appropriate filter and timer
- Burning position : horizontal  $\pm 10^\circ$  for double ended types : universal for single ended types
- Do not touch the quartz envelope with bare fingers
- Pinch temperature : max 350°C
- Bulb temperature : min 750°C, max 950°C

### PRODUCT OVERVIEW

Ordering number	0024221
EAN code	5410288242217
Colour temperature (K)	0
Nominal average life (h)	600
Cap/Base	Cable
Lamp Diameter (mm) - D	25.5
Watt (W)	1000
Type	SHP
Lamp Length (mm) - C	139
Voltage (V)	0

## PureBronze Suntanning - High Pressure HID

PureBronze PBO 1000W C 400 V

**0024221**

### DATA TABLE

#### General data

Ordering number	0024221
Nominal average life (h)	600
Ballast required	
EAN code	5410288242217
IEC Reference	
IEC Reference 2	
IEC Reference 3	
Cap/Base	Cable
Type	SHP
Special purpose lamp	Yes
Transformer required	
Unit case	10
Product name	PureBronze PBO 1000W C 400 V
Average rated life (h)	600
Long description	Features Short irradiation and exposure times Ozone free construction Long-life types offer outstanding UV-A maintenance out to 1000 hours Built according to DIN-EN-ISO 9001 Special versions available upon request Complete PBF range also available Applications Domestic cosmetic facial tanning Professional facial, half body and full body units Short intense tanning sessions DIRECTIONS FOR USE Only use in tanning devices equipped with appropriate filter and timer Burning position : horizontal $\pm 10^\circ$ for double ended types : universal for single ended types Do not touch the quartz envelope with bare fingers Pinch temperature : max 350°C Bulb temperature : min 750°C, max 950°C

#### Optical data

Colour temperature (K)	0
Rated luminous flux (lm)	0

#### Electrical data

Current (A)	0
Watt (W)	1000
Rated watt (W)	1000
Voltage (V)	0

## PureBronze Suntanning - High Pressure HID

PureBronze PBO 1000W C 400 V

**0024221**

### Physical data

Packaging outer height (cm)	12
Packaging single height (cm)	5.3
Lamp Diameter (mm) - D	25.5
Lamp Length (mm) - C	139
Packaging outer length (cm)	28.6
Packaging single length (cm)	17
Packaging outer width (cm)	1.8
Packaging single width (cm)	5.3



## PureBronze Suntanning - High Pressure HID

PureBronze PBO 1000W C 400 V

0024221

### TECHNICAL DRAWINGS

