

PureBronze Suntanning - High Pressure HID

PureBronze PBO 400W SL

0024201



Range features

- Features
- Short irradiation and exposure times
- Ozone free construction
- Long-life types offer outstanding UV-A maintenance out to 800 hours
- Special versions available upon request
- Complete PBF range also available
-
- Applications
- Domestic cosmetic facial tanning
- Professional facial, half body and full body units
- Short intense tanning sessions
-
- Directions For Use
- Only use in tanning devices equipped with appropriate filter and timer
- Burning position: horizontal $\pm 10^\circ$ for double ended types : universal for single ended types
- Do not touch the quartz envelope with bare fingers
- Pinch temperature: max 350°C
- Bulb temperature: min 750°C, max 950°C



PRODUCT OVERVIEW

Ordering number	0024201
Cap/Base	R7s long
Type	SHP
EAN code	5410288242019
Colour temperature (K)	0
Luminous flux (Rated) (lm)	0
Watt (Nominal) (W)	250-500
Voltage (V)	0

PureBronze Suntanning - High Pressure HID

PureBronze PBO 400W SL

0024201

DATA TABLE

General data

Ordering number	0024201
Average life (Nominal) (h)	600
Cap/Base	R7s long
Type	SHP
EAN code	5410288242019
Long description	Features . Short irradiation and exposure times . Ozone free construction . Long-life types offer outstanding UV-A maintenance out to 800 hours . Special versions available upon request . Complete PBF range also available . . Applications . Domestic cosmetic facial tanning . Professional facial, half body and full body units . Short intense tanning sessions . . Directions For Use . Only use in tanning devices equipped with appropriate filter and timer . Burning position: horizontal $\pm 10^\circ$ for double ended types : universal for single ended types . Do not touch the quartz envelope with bare fingers . Pinch temperature: max 350°C . Bulb temperature: min 750°C, max 950°C
Product name	PureBronze PBO 400W SL
Lamp mercury content (mg)	9.3
Special purpose lamp	Yes
Sales pack quantity	10

Optical data

Colour temperature (K)	0
Luminous flux (Rated) (lm)	0

Electrical data

Watt (Nominal) (W)	250-500
Voltage (V)	0
Current (A)	0

Physical data

Weight (kg)	0.01
Lamp Length (mm) - C/L	117.9
Max. Lamp Diameter (mm) - D	14
Single packaging type	Box/Sleeve
Single package dimensions (L x W x H) (cm)	17.00 x 4.50 x 4.50
Inner package dimensions (L x W x H) (cm)	23.00 x 18.00 x 10.00
Inner package net weight (kg)	0.12
Outer package dimensions (L x W x H) (cm)	51.00 x 24.50 x 19.00