

PureBronze Suntanning - High Pressure HID

PureBronze PBO 500W C

0024211



- Features
- Short irradiation and exposure times
- Ozone free construction
- Long-life types offer outstanding UV-A maintenance out to 1000 hours
- Built according to DIN-EN-ISO 9001
- Special versions available upon request
- Complete PBF range also available
-
- Applications
- Domestic cosmetic facial tanning
- Professional facial, half body and full body units
- Short intense tanning sessions
-
- DIRECTIONS FOR USE
- Only use in tanning devices equipped with appropriate filter and timer
- Burning position : horizontal $\pm 10^\circ$ for double ended types : universal for single ended types
- Do not touch the quartz envelope with bare fingers
- Pinch temperature : max 350°C
- Bulb temperature : min 750°C, max 950°C

PRODUCT OVERVIEW

Ordering number	0024211
EAN code	5410288242118
Colour temperature (K)	0
Nominal average life (h)	600
Cap/Base	Cable
Lamp Diameter (mm) - D	17
Voltage (V)	0
Type	SHP
Lamp Length (mm) - C	114
Watt (W)	300-600

PureBronze Suntanning - High Pressure HID

PureBronze PBO 500W C

0024211

DATA TABLE

General data

Ordering number	0024211
Nominal average life (h)	600
Ballast required	
EAN code	5410288242118
IEC Reference	
IEC Reference 2	
IEC Reference 3	
Cap/Base	Cable
Type	SHP
Special purpose lamp	Yes
Transformer required	
Unit case	50
Product name	PureBronze PBO 500W C
Average rated life (h)	600
Long description	Features Short irradiation and exposure times Ozone free construction Long-life types offer outstanding UV-A maintenance out to 1000 hours Built according to DIN-EN-ISO 9001 Special versions available upon request Complete PBF range also available Applications Domestic cosmetic facial tanning Professional facial, half body and full body units Short intense tanning sessions DIRECTIONS FOR USE Only use in tanning devices equipped with appropriate filter and timer Burning position : horizontal $\pm 10^\circ$ for double ended types : universal for single ended types Do not touch the quartz envelope with bare fingers Pinch temperature : max 350°C Bulb temperature : min 750°C, max 950°C

Optical data

Colour temperature (K)	0
Rated luminous flux (lm)	0

Electrical data

Current (A)	0
Voltage (V)	0
Watt (W)	300-600

PureBronze Suntanning - High Pressure HID

PureBronze PBO 500W C

0024211

Physical data

Packaging outer height (cm)	19.2
Packaging single height (cm)	4.5
Lamp Diameter (mm) - D	17
Lamp Length (mm) - C	114
Packaging outer length (cm)	50
Packaging single length (cm)	17
Packaging outer width (cm)	25
Packaging single width (cm)	4.5



PureBronze Suntanning - High Pressure HID

PureBronze PBO 500W C

0024211

TECHNICAL DRAWINGS

