



1



2



3

Artikel-Nummer	Bestellzeichen Code Référence	Leistungsaufnahme Wattage Puissance absorbée	Abmessungen (max.) Dimensions (max.)					Bild Picture Image	Sockel Base Culot	Versandinheit box quantity Unité d'Emballage
			W	l mm	a mm	b mm	d mm			
<b>Ralutec, Sockel G23 in Sonderlichtfarben / Ralutec, base G23 in special light colours</b> <b>Ralutec, culot G23 en couleurs spéciales</b>										
313 12179	<b>Ralutec 7W/78/G23</b>	7	115	97	27	12	1	G23	50	
313 12180	<b>Ralutec 9W/71/G23</b>	9	145	127	27	12	1	G23	50	
313 12181	<b>Ralutec 9W/78/G23</b>	9	145	127	27	12	1	G23	50	
313 12182	<b>Ralutec 11W/78/G23</b>	11	215	197	27	12	1	G23	50	
<b>Ralutec/E, Sockel 2G7 in Sonderlichtfarben / Ralutec/E, base 2G7 in special light colours</b> <b>Ralutec/E, culot 2G7 en couleurs spéciales</b>										
313 12184	<b>Ralutec/E 9W/78/2G7</b>	9	145	126	27	12	2	2G7	50	
313 12682	<b>Ralutec/E 11W/78/2G7</b>	11	215	197	27	12	2	2G7	50	
<b>Ralutec long, Sockel 2G11 in Sonderlichtfarben / Ralutec long, base 2G11 in special light colours</b> <b>Ralutec long, culot 2G11 en couleurs spéciales</b>										
313 12185	<b>Ralutec long 18W/71/2G11</b>	18	225	197	38	12	3	2G11	10	
313 12186	<b>Ralutec long 18W/78/2G11</b>	18	225	197	38	12	3	2G11	10	

Bestellzeichen Type Référence	Strahlerstrom Lamp current Courant de brûleur	UV-Strahlungsleistung (350-400 nm) UV Radiation power (350-400 nm) UV/Puissance de rayonnement (350-400 nm)		Brennstellung Burning position Position de fonctionnement	Wirtschaftliche Lebensdauer Economic lifetime Durée de vie économique
		W	W		
<b>Ralutec 7W/78/G23</b>	0,175	1,4	-	s180	1 000
<b>Ralutec 9W/71/G23</b>	0,170	-	2,3	s180	1 000
<b>Ralutec 9W/78/G23</b>	0,170	1,7	-	s180	1 000
<b>Ralutec 11W/78/G23</b>	0,155	2,3	-	s180	1 000
<b>Ralutec/E 9W/78/2G7</b>	0,170	1,7	-	s180	1 000
<b>Ralutec/E 11W/78/2G7</b>	0,155	2,3	-	s180	1 000
<b>Ralutec long 18W/71/2G11</b>	0,370	-	4,2	s180	1 000
<b>Ralutec long 18W/78/2G11</b>	0,370	2,8	-	s180	1 000