

Special Lighting Starters

Range of glow switch starters for igniting fluorescent tanning lamps with electromagnetic ballast 2- pin igniter in plastic (flame-retardant polycarbonate) canister and radiointerference suppression capacitor

Product Features

- Premium reliability with less than 100 early failures per million products (<100 ppm)
- Premium reliability with 10000 swiches guaranteed
- No hazardous radioactive isotopes used for activating the glow switch
- Lead-free and compliant with European RoHS legislation (Reduction of Hazardous Substances)
- Secure, safe and fast ignition on both inductive (L) and capacitive (LC) lighting systems acc. to IEC 60155
- Controlled preheating of the lamp filaments and sufficient pulse voltage for longer lamp life (>25% compared with cheap starters)

Product Benefits

- Premium quality ensures trouble-free operation; extremely low early replacements reduce maintenance costs
- · The world's only starters which are radioactive

free and lead free, avoiding hazardous substances in manufacturing and recycling

- Secure, safe and fast lamp ignition on both L and LC systems according to IEC 60155
- · Safe end- of- life behaviour prevents safety issues
- UV-resistant canister protects against unsafe conditions

Application

- Fluorescent lamp systems with conventional electromagnetic ballast using TL-D (T8), TL (T12) tanning lamps
- CLEO starters suitable for 220/240 V~, 25-100 W single applications
- CLEO POWER starters suitable for 230/240 V~, 100-180 W single applications
- Starter replacement recommended when replacing fluorescent lamps

Order code	Full product name
765055 28	S12 80-140W 220-240V UNP
750105 28	S16 70-125W 240V UNP
750105 31	S16 70- 125W 240V UNP

Legend

Column	Value	Explanation
Packing Type	UNP	Unpacked



Basic specifications - Special Lighting

Order code	Rated	Voltage	Packing	Packing	System	Cap-Base	Colour	Execution	Non Reclosure
	Lamp		Type	Configur ation	Descripti on	Informati on	of the		Voltage
	Wat-						Housing		
	tage								
765055 28	80-140W	220-240 V	UNP	1000	SINGLE	2 Pins	White	White	135
750105 28	70- 125W	240V	UNP	1000	SINGLE	2 Pins	White	White	170
750105 31	70- 125W	240V	UNP	20X10BO X	SINGLE	2 Pins	White	White	170



STARTX S12



STARTX S16

