




PAR36 6V 30W

**FEATURES**

- Pressed glass reflector lamps
- Beam patterns: from very narrow spot through wide angle floods
- Consistency from lamp to lamp
- Economical light source for effects
- Halogen version delivers maintained beam intensity throughout life

**APPLICATIONS**

- Entertainment and Architectural applications
- Displays
- Museums
- Exhibitions
- Gardens
- Discos

**DIRECTIONS FOR USE**

- Easy handling
- Can be used with very economical fixtures (PAR cans)



Item description	ANSI	LIF	Voltage	Watt	Beam type	Approx. Beam Spread 10% Peak CD	Base
			V	W			
PAR 36 6,4V 30W (4515)	-	-	6.4	30	Spot	5x5	Screw Terminal
PAR 36 12,8V 30W (H 4405)	-	-	12.8	30	Spot	6x5	Screw Terminal
PAR 36 12V 50W NSP	-	-	12	50	Narrow Spot	11x10	Screw Terminal
PAR 36 12V 50W NFL	-	-	12	50	Wide Flood	30x25	Screw Terminal

Item description	Dimensions		Peak Intensity cd	Colour temp. K	Rated Av. Life h	Burning Position	Packing Quantity	Ordering Code
	A Diameter mm	C MOL mm						
PAR 36 6,4V 30W (4515)	114	70	55000	3200	100	Any	12	9061531
PAR 36 12,8V 30W (H 4405)	114	70	50000	3200	100	Any	12	9020167
PAR 36 12V 50W NSP	114	70	11000	3000	2000	Any	12	0060501
PAR 36 12V 50W NFL	114	70	1300	3000	2000	Any	12	0060502