

PAR 64 Mains Voltage

PAR 64 CP88 240V 500W MFL

9061148



Range features

- Pressed glass reflector lamps
- Extremely powerful beam
- Halogen inner capsule, for 100% lumen maintenance through life
- Beam patterns: from very narrow spot through wide angle floods
- Consistency from lamp to lamp
- Instant replaceability without the need to re-focus and re-aim fixtures
- Double internal fused for end of life safety
- Applications
- Theatre lighting
- TV and studio
- Entertainment and Architectural applications
- Displays
- Museums
- Churches
- Towers
- Exhibitions
- Gardens
- Discos



PRODUCT OVERVIEW

Ordering number	9061148
Average life (Rated) (h)	300
Type	PAR 64
EAN code	5410288611488
Beam angle(°)	Medium Flood
Colour temperature (K)	3200
Watt (Nominal) (W)	500

PAR 64 Mains Voltage

PAR 64 CP88 240V 500W MFL

9061148

DATA TABLE

General data

Ordering number	9061148
Average life (Rated) (h)	300
Type	PAR 64
EAN code	5410288611488
Long description	Pressed glass reflector lamps. Extremely powerful beam. Halogen inner capsule, for 100% lumen maintenance through life. Beam patterns: from very narrow spot through wide angle floods. Consistency from lamp to lamp. Instant replaceability without the need to re-focus and re-aim fixtures. Double internal fused for end of life safety. Applications. Theatre lighting. TV and studio. Entertainment and Architectural applications. Displays. Museums. Churches. Towers. Exhibitions. Gardens. Discos
Product name	PAR 64 CP88 240V 500W MFL
Burning position	Any
Sales pack quantity	6

Optical data

Beam angle (°)	Medium Flood
Colour temperature (K)	3200
Peak intensity (cd)	65000

Electrical data

Watt (Nominal) (W)	500
---------------------------	-----

Physical data

Weight (kg)	0.74
--------------------	------

PAR 64 Mains Voltage

PAR 64 CP88 240V 500W MFL

9061148

TECHNICAL DRAWINGS

