



MASTER TL-D Xtra

MASTER TL-D Xtra 18W/865 1SL

This TL-D Xtra lamp offers a longer lifetime and guarantees fewer early failures. This results in low maintenance costs and saves on expensive spot replacement. It is therefore suitable for places where lamp replacement is expensive due to high ceilings or disturbance of operations. This lamp can be operated on existing gear or dedicated HF Xtreme gear.

Product data

• General Characteristics

Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Cap-Base Information	Green Plate
Bulb	T8 [26 mm]
Life to 10% failures EM	30000 hr
Life to 10% fail Preheat EL,3h	47000 hr
Life to 10% fail Nonpreh EL,3h	19000 hr
Life to 50% failures EM	36000 hr
Life to 50% fail Preheat EL,3h	55000 hr
Life to 50% fail Nonpreh EL,3h	22000 hr
LSF EM 2000h Rated, 3h cycle	100 %
LSF EM 4000h Rated, 3h cycle	100 %
LSF EM 6000h Rated, 3h cycle	100 %
LSF EM 8000h Rated, 3h cycle	100 %
LSF EM 12000h Rated,3h cycle	100 %
LSF EM 16000h Rated,3h cycle	100 %
LSF EM 20000h Rated,3h cycle	100 %

• Light Technical Characteristics

Color Code	865 [CCT of 6500K]
Color Rendering Index	85 Ra8

Color Designation (text)	Cool Daylight
Color Temperature	6500 K
Luminous Flux EM 25°C, Rated	1250 Lm
Luminous Flux EM 25°C, Nominal	1250 Lm
Lum Efficacy Rated EM 25°C	71 Lm/W
LLMF EM 2000h Rated	96 %
LLMF EM 4000h Rated	95 %
LLMF EM 6000h Rated	94 %
LLMF EM 8000h Rated	93 %
LLMF EM 12000h Rated	92 %
LLMF EM 16000h Rated	91 %
LLMF EM 20000h Rated	90 %
Design Temperature	25 C
Chromaticity Coordinate X	314 -
Chromaticity Coordinate Y	336 -

• Electrical Characteristics

Lamp Wattage	18 W
Lamp Wattage EM 25°C, Nominal	18 W
Lamp Wattage EM 25°C, Rated	17.7 W



MASTER TL-D Xtra

Lamp Voltage EM 25°C	56 V
Lamp Current EM 25°C	0.370 A
Dimmable	Yes

• Environmental Characteristics

Energy Efficiency Label (EEL)	A
Mercury (Hg) Content	3.0 mg
Energy consumption kWh/1000h	22 kWh

• Product Dimensions

Base Face to Base Face A	589.8 (max) mm
Insertion Length B	594.5 (min), 596.9 (max) mm

Overall Length C	604.0 (max) mm
Diameter D	28 (max) mm

• Product Data



Order code	927980486514
Full product code	927980486514
Full product name	MASTER TL-D Xtra 18W/865 1SL
Order product name	MASTER TL-D Xtra 18W/865 1SL
Pieces per pack	1
Packing configuration	25
Packs per outerbox	25
Bar code on pack - EAN1	8711500892812
Bar code on outerbox - EAN3	8711500892829
Logistic code(s) - 12NC	927980486514
ILCOS code	FD-18/40/1B-E-G13
Net weight per piece	80.100 gr

Warnings and Safety

- Philips HF Xtreme gear ensures longest lifetime.
- To achieve lifetimes as published for 100% operation, dimming below 30% should not be applied.

- In the case of electromagnetic gear you are strongly advised to use only Philips S10 starters in order to achieve the published lifetimes, and to install new S10 starters when relamping.

Dimensional drawing





G13

MASTER TL-D Xtra 18W/865 1SL

Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL-D Xtra 18W/865	589.8	594.5	596.9	604.0	28

Photometric data



© 2013 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2013, July 4
data subject to change