

# TUV T8

## TUV 25W 1SL

TUV T8 lamps are double-ended UVC (germicidal) lamps used in professional water and air disinfection units. TUV T8 lamps offer almost constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy. Moreover, they have a long and reliable lifetime, which allows maintenance to be planned for in advance.

### Product data

## • General Characteristics

System Description Cap-Base G13
Bulb T26
Main Application Disinfection
Useful Life 9000 hr

### • Electrical Characteristics

Lamp Wattage 25 W
Lamp Wattage Technical
Lamp Voltage 48 V
Lamp Current 0.6 A

### • Environmental Characteristics

Mercury (Hg) 2.0 mg Content

## • Light Technical Characteristics

Color Designation (text)

## • UV-related Characteristics

UV-C Radiation 7 W

## • Product Dimensions


Base Face to Base 437.4 (max) mm
Face A
Insertion Length B
Overall Length C
Diameter D
437.4 (max) mm
442.1 (min), 444.5 (max) mm
451.6 (max) mm
28 (max) mm

## • Product Data

Order code 928039404005 928039404005 Full product code Full product name TUV 25W 1SL Order product name TUV 25W 1SL/25 Pieces per pack Packing configuration 25 Packs per outerbox 25 Bar code on pack -8711500641618 EAN1 8711500641625 Bar code on outerbox - EAN3 928039404005 Logistic code(s) -12NC Net weight per piece 69.900 gr




## Dimensional drawing




Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TUV TL-D 25W	437.4	442,1	444.5	451.6	28



## Photometric data







Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.