

## Technical Information

No. FO 4962

Edition: 08/05 - subject to change

Substitutes: Edition 07/00

Status: valid

## Xenon Short Arc Lamp

# XBO<sup>®</sup> 450 W/2 OFR


### ■ Product description

The OSRAM XBO<sup>®</sup> 450 W/2 OFR is a DC-operated lamp that is especially suited for applications requiring excellent arc stability and a high luminance. The OSRAM XBO<sup>®</sup> 450 W/2 OFR is designed for vertical burning position ( /2 = compact ).

### ■ Technical data

Order reference	XBO <sup>®</sup> 450 W/2 OFR	
Rated lamp wattage	W	450
Rated lamp voltage	V	17
Rated lamp current (=)	A	25
Current control range	A	17 - 30
Ignition voltage	kV <sub>s</sub>	33
Min. open circuit voltage for cold / hot ignition	V	60 / 70
Luminous flux	lm	13,000
Luminous intensity	cd	1,300
Average luminance	cd/cm <sup>2</sup>	35,000
Luminous area w x h *)	mm	0.9 x 2.7
Electrode gap e (cold)	mm	3.0
Lamp length (overall) l <sub>1</sub>	mm	max. 177
Lamp length l <sub>2</sub>	mm	---
LCL a	mm	79
Bulb diameter d	mm	29
Average service life	h	2,500
Warranty	h	2,000
Base	Cathode	SK 19/36
	Anode	SK 19/36

\*) w = luminance half width value; h = height of luminance area (corresponds to electrode gap , hot)



### ■ Lamp operation

Maximum permissible base temperature	230 °C
Cooling	forced cooling / fan
Min. air flow velocity around discharge vessel	3 m/s
Magnetic arc stabilization	no
Burning position	s 30 (vertical ± 30° ; anode up)