
ITT 2500 W 400 V-0826 K

HALOTHERM | Infrared halogen lamps with white reflector



Areas of application

- Manufacture of PET bottles
- Coil coating
- Professional grills and heated counters in restaurants

Product benefits

- High efficiency
- Precise controllability
- Long lamp life
- Short response time

Product features

- Short-wave infrared halogen lamps (IR-A) for technical applications
- Maximum radiation at a wavelength of about 1,100 nm



Product datasheet

Technical data


Electrical data

Nominal wattage	2500.00 W
Nominal voltage	400 V
Construction voltage	400.00 V
Lamp current	6.3 A
Nominal current	6.3 A

Photometrical data

Color temperature	2500 K
-------------------	--------

Dimensions & weight



Diameter	11.0 mm
Length	380.0 mm
Filament length	285.00 mm
Cable length	200.0 mm

Lifespan

Lifespan	5000 h
----------	--------

Additional product data

Base (standard designation)	K9x15/21
Connector: Presence	Yes

Capabilities

Burning position	p15
------------------	-----

Country specific information

Product datasheet

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321206336	OSRHALOTT250026K	-	-	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321206336	ITT 2500 W 400 V-0826 K	Folding carton box 1	26 mm x 26 mm x 378 mm	0.26 dm ³	75.00 g
4008321206343	ITT 2500 W 400 V-0826 K	Shipping carton box 12	395 mm x 90 mm x 125 mm	4.44 dm ³	997.00 g
4008321676610	ITT 2500 W 400 V-0826 K	Folding carton box 1	26 mm x 26 mm x 403 mm	0.27 dm ³	70.00 g
4008321676627	ITT 2500 W 400 V-0826 K	Shipping carton box 12	395 mm x 120 mm x 95 mm	4.50 dm ³	997.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.