

LED SUPERSTAR CLASSIC P 40 DIM 6 W/827 E27 CS

LED SUPERSTAR CLASSIC P | Dimmable LED lamps, classic mini-ball shape



Areas of application

- General illumination
- Domestic applications
- Outdoor applications only in suitable luminaires

Product benefits

- Lower thermal output (compared with the standard reference product)
- Very low energy consumption
- Shockproof and vibration-proof thanks to LED technology
- Extremely long life
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Simple direct replacement for conventional incandescent lamps

Product features

- Professional LED lamps for line voltage
- Available with E14 or E27 screw base
- Dimmable (with many common dimmers, see also www.osram.com/dim)
- Mercury-free lamps





Technical data

Electrical data

Rated wattage	5.70 W	
Nominal wattage	6.00 W	
Nominal voltage	220240 V	
Operating frequency	5060 Hz	
Power factor λ	> 0.50	
Claimed equiv. conventional lamp power	40 W	


Photometrical data

Nominal luminous flux	470 lm
Rated luminous flux	470 lm
Color temperature	2700 К
Color rendering index Ra	80
Light color (designation)	Warm White
Standard deviation of color matching	≤6 sdcm

Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & weight



Overall length	80.0 mm
Diameter	43.0 mm
Outer bulb	P40
Length	80.0 mm

Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000
Lumen main.fact.at end of nom.life time	0.70
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E27
Lamp mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Appropriate disposal acc. to WEEE	Yes

Capabilities

Dimmable	Yes ¹⁾
----------	-------------------

 $^{1)}\ {\rm With}\ {\rm many}\ {\rm common}\ {\rm dimmers},\ {\rm see}\ {\rm also}\ {\rm www.osram.com/dim}$


Certificates & standards

Energy efficiency class	A+	
Energy consumption	6 kWh/1000h	


Country specific categorizations

ILCOS	DRBP/C-6,2-220-240-E27-43/89	
Order reference	SSTCLP40AD6W/82	

Light Distribution



Spectral power distribution



Others graphics

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899904422	LED SUPERSTAR CLASSIC P 40 DIM 6 W/827 E27 CS	Shipping carton box 6	274 mm x 72 mm x 133 mm	2.62 dm ³	606.00 g

January 8, 2016, 05:38:53 LED SUPERSTAR CLASSIC P 40 DIM 6 W/827 E27 CS

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For further products and actual information concerning LED lamps see

www.osram.com/ledlamps

For Guarantee see

www.osram.com/guarantee

For dimming conformity see

www.osram.com/DIM

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.